



ILLINOIS DEPARTMENT OF NATURAL RESOURCES

Office of Oil and Gas Resource Management
One Natural Resources Way Springfield, Illinois 62702-1271



**HIGH VOLUME HORIZONTAL HYDRAULIC FRACTURING
PERMIT APPLICATION HVHFF-10**

References to "1-xx" or "§1-xx" are to the Hydraulic Fracturing Regulatory Act., 225 ILCS 732/1-1 et seq. References to "240.xxx" and "245.xxx" are to 62 Ill. Admin. Code 240 and 245, respectively.

Attachment: WellSiteSafetyPlan

Please save attachment and use the file name above.

Well Site Safety Plan §1-35(b)(12); 245.210(a)(12). Provide a copy of the OSHA-compliant plan for the safety measures you will employ during high volume horizontal hydraulic fracturing operations to protect persons on site and the general public. Please address safety measures for an emergency, identify the presence of any hazardous materials used or stored at the site, and provide contact information for the applicant and for all appropriate emergency responders. If any part of the well or well site is in an area identified by the U.S. Geological Service as having a 2% or greater probability of exceedance in 50 years of peak ground acceleration of 0.4 standard gravity or more, identify measures you will take to protect the components in this plan against earthquakes of M4.5 or more.

Have you provided a copy of this plan to the county or counties in which fracturing operations will be occurring? YES NO If "NO" provide, within 15 calendar days after submitting the permit application to the Department, a copy of the plan to the county or counties in which hydraulic fracturing operations will occur as required by § 1-35(12).



**Woolsey Operating Company, LLC
125 North Market, Suite 1000
Wichita, Kansas, 67202**

**Well Site Safety and Health Plan
Woodrow #1H-410308-193**

Raymond Gibson

Prepared by:
SRP Environmental, LLC
(318) 222-2364

February 2, 2017

Date

Mark Sooter

Approved by:
Vice President of Business Development
Woolsey Companies, Inc. LLC
(Phone)

May 5, 2017

Date

Table of Contents

	<u>Page #</u>
Section 1: Introduction	
1.1 Purpose and Objectives _____	1
1.2 Plan Updates and Revisions _____	1
Section 2: Site Description	
2.1 Work Area Description _____	2
Section 3: Hazard/Risk Analysis	
3.1 Chemical Hazards _____	7
3.1.1 Skin Contact _____	7
3.1.2 Eye Contact _____	7
3.1.3 Inhalation _____	7
3.2 Physical Hazards _____	7
3.2.1 Heat and Cold Stress _____	8
3.2.2 Slips, Trips, and Falls _____	8
3.2.3 Working Near Heavy Equipment _____	8
3.2.4 Noise _____	8
3.2.5 Handling Heavy Objects _____	8
3.2.6 Combustible and Flammable Materials/Liquids _____	8
3.2.7 Fire Protection _____	9
3.2.8 Electrical Hazards _____	9
3.2.9 Confined Space Entry _____	9
3.2.10 Naturally Occurring Radioactive Material _____	9
3.2.10.1 Scope of Field Testing _____	9
3.2.10.2 Field Sampling Activities _____	10
3.2.10.3 Sampling Methods _____	10
3.2.10.4 Sampling Equipment Decontamination _____	11
3.3 Biological Hazards _____	11
3.3.1 Insects _____	12
3.3.2 Vermin _____	12
Section 4: Responsibilities	
4.1 Woolsey Responsibilities _____	12
4.2 Chain of Command _____	12
4.2.1 Corporate Health and Safety Manager _____	12
4.2.2 Site Safety and Health Officer _____	12
4.2.3 Public Visitors _____	12

Section 5: Health and Safety Training

5.1 Site-Specific Health and Safety Training _____ 13
5.2 Hazard Communication _____ 14
5.3 Daily Health and Safety Meetings _____ 14
5.4 Training Records _____ 15

Section 6: Personal Protective Equipment

6.1.1 Eye Protection _____ 15
6.1.2 Hard Hats _____ 15
6.1.3 Shoes _____ 15
6.1.4 Shirts and Pants _____ 15
6.1.5 Nitrile Gloves _____ 15
6.1.6 Hearing Protection _____ 15
6.1.7 Respiratory Protection _____ 15
6.1.8 Vehicle Safety _____ 16
6.1.9 Visitor Protection _____ 16

Section 7: Medical Surveillance

7.1 Purpose and Scope _____ 16
7.2 Responsibilities _____ 17
7.3 Medical Release Forms _____ 17
7.4 Employment-Related Injury or Illness Medical Evaluations _____ 17
7.5 Return to Work Examinations _____ 17
7.6 Access to Medical Records and Exposure Data _____ 17

Section 8: Air Monitoring

Section 9: Heat and Cold Stress Prevention

9.1 Heat Stress Prevention _____ 18
9.2 Cold Stress Prevention _____ 18

Section 10: Standard Work Practices

10.1 General HVVHF Activities _____ 19
10.2 Working Around Heavy Equipment _____ 19
10.3 Underground Utilities _____ 20
10.4 Spill Response _____ 20
10.5 Site Safety Practices _____ 20
10.6 Material Lifting _____ 21
10.7 Contingency Plans _____ 21

Section 11: Site Control and Personal Hygiene _____ 21

Section 12: Accident and Illness Prevention

12.1 Introduction _____ 22
12.2 Safety Promotion _____ 22

12.3 Medical and First Aid Requirements _____ 22

Section 13: Emergency Response and Contingency Procedures

13.1 Emergency Medical Facility _____ 23
13.2 Medical Emergencies _____ 23
13.3 Exposure/Injury Reporting _____ 24
 13.3.1 Accident Reporting and Investigation _____ 24
 13.3.2 Follow-Up _____ 25
 13.3.3 Occupational Injuries and Illnesses _____ 25
13.4 Emergency Evacuation Plan _____ 25
13.5 Fire and Explosion Procedures _____ 25
13.6 Spill Response Procedures _____ 28
 13.6.1 Spill Response _____ 28
13.7 Equipment and Training _____ 29

Attachment A: Safety Data Sheets

Attachment B: Heat and Cold Stress Guidelines

Attachment C: Field Health and Safety Meeting Record

Attachment D: Signature Form

Attachment E: Fugitive Dust Control Plan

Attachment F: Respiratory Protection Program

Tables

3-1 Hazardous Materials _____ 7
3-1 NORM Detection Equipment _____ 10
13-1 Emergency Contacts _____ 29

Figures

2-1 Work Site Description _____ 2
2-2 Site Location Map _____ 3
2-3 Site Residence Setback _____ 4
2-4 Site Waterway Setback _____ 5
2-5 Site Water Well Setback _____ 6
13-1 Map to Emergency Medical Facility _____ 30

Abbreviations and Acronyms

°C	degrees Celsius
°F	degrees Fahrenheit
ACGIH	American Conference of Governmental Industrial Hygienists
AIHA	American Industrial Hygiene Association
ANSI	American National Standard Institute
APR	air purifying respirator
AQC	air quality control
CFR	Code of Federal Regulations
CHSM	Corporate Health and Safety Manager
CIH	Certified Industrial Hygienist
CNS	central nervous system
CPR	cardiopulmonary resuscitation
CSP	Certified Safety Professional
dB	decibel
dBA	decibel average
EPA	U.S. Environmental Protection Agency
H&S	health and safety
HSP	health and safety program
HVHF	High Volume Horizontal Hydraulic Fracturing
IDLH	immediately dangerous to life or health
JSA	job safety analysis
mg/m ³	milligrams per cubic meter
MSA	Mine Safety Appliance Company
NFPA	National Fire Protection Agency
NIOSH	National Institute for Occupational Safety and Health
NORM	naturally occurring radioactive material
NRR	noise reduction rating
OSHA	Occupational Safety and Health Administration
OU	operable unit
OCV	Operations Control Van
PEL	permissible exposure limit
PID	photoionization detector
PM	project manager
PPE	personal protective equipment
ppm	parts per million
SDS	safety data sheet
SSHO	site safety and health officer
SSHP	site safety and health plan
STEL	short-term exposure limit
TLV	threshold limit value
TWA	time-weighted average

WGBT

Wet-Bulb Globe Temperature

This Page Intentionally Left Blank

Section 1: Introduction

1.1 Purpose and Objectives

This Site Safety and Health Plan (SSHP) addresses the minimum safety, health, and emergency response requirements for Woolsey Operating Company, LLC (Woolsey) during High Volume Horizontal Hydraulic Fracturing (HVHHF) operations. These HVHHF activities have the potential to result in employee and general public exposure to potential health and safety hazards. Woolsey has developed this SSHP to mitigate these concerns. Woolsey will obtain full compliance with this plan by its employees and subcontractors. All HVHHF personnel and subcontractors are required to adhere to the SSHP requirements. Trespassers not associated with the field activities will be discouraged from entering the site.

The SSHP objectives are to ensure that all necessary precautions for HVHHF activities are in place and that appropriate health and safety procedures are followed at all times to protect personnel and the general public; to prevent damage, injury, or loss of property and equipment; and to respond quickly and effectively to activity-related emergencies.

Before commencing HVHHF activities, all company and subcontractor employees assigned to the project will receive a copy of the SSHP and will be trained in its provisions. A copy of the SSHP will be kept on site in the Operations Control Van (OCV) at all times. The site safety and health officer (SSHO) (or alternate SSSH) will be responsible for ensuring that the SSHP requirements are understood by field personnel and that site activities are performed with the utmost regard for the safety and health of all personnel, subcontractors and the general public involved. Woolsey is only responsible for the health, safety, and emergency response activities related to its activities. Woolsey and its subcontractors are required to conduct job safety analysis (JSAs) summarizing the potential hazards that may be encountered while conducting the HVHHF tasks for this project. The JSAs will also provide a summary of the precautionary and preventative measures associated with these hazards. The requirements of this section are based on current information and understanding of the existing impacts at the site. Woolsey will assess all aspects of safety and health protection, including individual activities and long-term health monitoring, and will continually evaluate future health and safety requirements.

1.2 Plan Updates and Revisions

This SSHP will be evaluated on an annual basis to ensure compliance with local, state, and federal regulations. The plan will be updated based upon the review findings.


WOOLSEY OPERATING COMPANY, LLC

WOODROW #1H-410308-193

WHITE COUNTY, ILLINOIS



SCHMATIC of WELL PAD & HVHFF FLOW BACK OPERATIONS



Section 2: Site Description

Figure 2-1 Work Site Description




Figure 2-2: Site Location Map




Figure 2-3: Site Residence Setback




Figure 2-4: Site Waterways Setback




Figure 2-5: Site Water Wells Setback

Section 3: Hazard/Risk Analysis

3.1 Chemical Hazards

Woolsey and subcontractor employees will be exposed to various chemicals throughout the duration of this project. Safety Data Sheets (SDSs) will be located in the OCV. A list of hazardous materials used or stored at the site during HVVHF activities is included in Table 3-1.

Table 3-1

TRADE NAME/MATERIAL
Hydrochloric Acid
Cronox AK-50
NE-6 Surfactant
Plexgel Breaker XPA/Plexbreak 134
Plexslick 957 FR-7
Ferriplex 66
Diesel

3.1.1 Skin Contact

One route of possible exposure is through skin contact. Acute exposure to these chemicals can produce skin irritation. The following PPE to protect against skin contact will be utilized by personnel during chemical handling activities:

- Nitrile disposable gloves
- Butyl-rubber gloves

3.1.2 Eye Contact

Safety glasses in accordance with American National Standard Institute (ANSI) Z87.1 will be worn for all site activities. Face splash shields will be worn during mixing or pouring of chemicals. A portable eyewash station will be present onsite during all activities. Location of the eyewash station will be checked prior to activities that require the use of face splash shields to ensure it is readily accessible.

3.1.3 Inhalation

Another possible route of exposure is inhalation of vapors and dust particles. Refer to the Fugitive Dust Control Plan (Attachment E) for potential inhalation hazards and controls.

3.2 Physical Hazards

Physical hazards will be present in all job areas. The SSHO (or alternate SSHO) will screen the area for physical hazards prior to beginning work. Multiple physical hazards may be present at the area.

3.2.1 Heat and Cold Stress

Seasonal site conditions should be considered for all HVVHF activities. For field personnel, heat stress is usually a result of protective clothing decreasing natural body ventilation, although it may occur at any time work is being performed at elevated temperatures. Factors that contribute to cold stress exposure include temperature, humidity, wind, sunlight, rain, snow, fog, exposure duration, clothing, and work activity. Thus, heat and cold stress prevention will be practiced in accordance with the techniques in Section 9 and in Attachment B of this SSHP.

3.2.2 Slips, Trips, and Falls

Possible site conditions including rough terrain and steep slopes may be encountered for all HVVHF activities. Slips, trips, and falls can be easily prevented by using common sense practices such as good housekeeping procedures, identifying tripping hazards and rectifying or avoiding them, and walking slowly with proper footwear on slippery surfaces.

3.2.3 Working near Heavy Equipment

Heavy equipment activities during will include the use of excavators, front loaders, and dump trucks. Hazards associated with heavy equipment activities include mechanical hazards associated with rotating and/or unsecured equipment or cables, tripping hazards, falling objects, electrical shock from surface or underground utility lines or electrical equipment, noise from operating equipment, burns which might be incurred using pressure washer equipment, and inhalation hazards associated with equipment exhaust, or dust.

3.2.4 Noise

Use of heavy equipment may expose the field team to noise levels that exceed the Occupational Safety and Health Administration (OSHA) permissible exposure limit (PEL) of 90 decibels average (dBA) for an 8-hour day. Exposure to noise can result in the following:

- Temporary hearing losses where normal hearing returns after a rest period
- Interference with speech communication and the perception of auditory signals
- Interference with the performance of complicated tasks
- Permanent hearing loss due to repeated exposure resulting in nerve destruction in the hearing organ

Since personal noise monitoring will not be conducted during the proposed activities, all personnel performing activities at the jobsite while heavy equipment and drilling equipment is in operation must wear either disposable earplugs or earmuffs, but all hearing protection must have a minimum noise reduction rating (NRR) of 27 decibels (dB). An ear protection station with a sign stating “Ear Protection Required” will be placed at the entry point.

3.2.5 Handling Heavy Objects

Use mechanical means for lifting whenever possible (i.e., forklift, lift gate, loader, etc.). Observe proper lifting techniques and use certified lift chains and appropriate load points. Obey sensible lifting limits (60 pound maximum per person manual lifting or 1/3 a person’s bodyweight, whichever is less).

3.2.6 Combustible and Flammable Materials/Liquids

FM/UL-approved flammable liquid containers, labeled with the content, will be used to store fuel.

All fuel containers will be stored at least 15 meters (50 feet) from any facilities and ignition sources or

stored inside an approved flammable storage cabinet.

ABC fire extinguishers will be located in each field vehicle and on all heavy equipment.

Post “NO SMOKING” signs in refueling areas and on fuel storage tanks.

Avoid parking vehicles in area of tall dry grass or other potentially combustible material

3.2.7 Fire Protection

The work site will at all times be equipped with a means of communication with the fire department (i.e., cell phone), a 20# ABC portable fire extinguisher, and a shovel.

Combustible material hazards may include materials near ignition sources (hot motor or exhaust system), and transfer and storage of flammable or combustible liquids (if a generator or other portable fueled equipment is used).

Only FM/UL-approved flammable liquid containers, labeled with the content, will be used to store fuel.

All fuel containers will be stored at least 15 meters (50 feet) from any facilities and ignition sources, or stored inside an approved flammable storage cabinet.

Fire suppression equipment will be staged in all areas where flammable materials are stored (i.e. fuel dispensing and storage locations).

3.2.8 Electrical Hazards

3.2.8.1 Electrical Installation

Woolsey employees will not conduct electrical installation activities.

3.2.8.2 Working near Energized Circuits

Per OSHA electrical regulations (29 Code of Federal Regulations [CFR] 1910.333), only "qualified" persons may work on energized electrical circuit parts or equipment or perform testing work on energized electrical circuits or equipment.

The OSHA standard further states that even qualified persons working near exposed energized electrical parts can't approach closer than 1 foot of a system that is over 300 volts (V) but not over 750V. The standard does allow for closer approaches by qualified personnel if personnel are wearing insulated gloves with the proper voltage rating. For this program, qualified personnel will wear rubber insulated gloves with a voltage rating of up to 1,000 V (Class O glove). Leather protector gloves will be worn over the rubber insulating gloves.

3.2.8.3 Lock-Out/Tag-Out

It is the responsibility of Woolsey employees and/or subcontractors to verify that all equipment is locked out in accordance with standard operating procedures before performing any maintenance or repair work on energized equipment. The source must be locked out; it is not enough to push the power switch to “off” and disconnect the breaker. Anyone can re-engage power under these circumstances. Locking out the power source is the only way to guarantee that the power will not be inadvertently reactivated.

3.2.9 Confined Space Entry

Woolsey employees will not enter into confined spaces.

3.2.10 Naturally Occurring Radioactive Material (NORM)

NORM might be released from oil and gas formations. Workers at risk of exposure include those who handle pipes and equipment that might have been contaminated with NORM. Sludge, drilling mud, and

pipe scales, for example, often contain elevated levels of NORM, and the radioactive materials might be moved from site to site as equipment and materials are reused. Disposal, reuse, and recycling of NORM might cause worker exposures.

Testing of black shale drill cuttings, flowback, surface waters, and soil will be conducted to determine levels the presence and levels of the following:

- Total dissolved solids
- Gross Alpha
- Gross Beta
- Radium-226
- Radium-228
- Potassium-40

Site characterization of radioactive materials in the soil and surface waters will be determined during the initial site sampling event.

3.2.10.1 Scope of Field Testing

Field screening activities will consist of using field measurement instruments to identify the presence and approximate amounts of NORM and TENORM in cutting pits (open and closed), flowback and produced water. Screening of solid and aqueous samples and swipes (smears) samples will also be performed.

Direct-read radiological survey instruments will be used throughout the HVHHF operations of the project for scanning and surveying of personnel, equipment, materials and general areas. The survey instruments will be operated and maintained by Woolsey personnel or qualified contractors. Additional equipment that may be used on-site will be maintained and operated by the operator's technician(s) or subcontractors. Proposed instruments, detectors, and equipment (or their equivalents) to be used on-site during field screening are listed below.

Table 3-2

Equipment Instrument	Detector	Parameter
Ludlum Model 2224, or equivalent	Ludlum Model 43-89, alpha/beta scintillator, or equivalent	Portable scaler/ ratemeter for detecting alpha and beta radiation
Ludlum Model 2221, or equivalent	Ludlum Model 44-10, gamma scintillator, or equivalent	Portable scaler/ ratemeter for detecting gamma radiation
Ludlum Model 2929, or equivalent	Ludlum Model 43-10-1, or equivalent	Table top counter for detecting alpha and beta radiation
Bicron Microrem, or equivalent	Internally-mounted plastic gamma scintillator	Portable exposure rate survey meter for gamma radiation
Ludlum Model 3, or equivalent	Ludlum Model 44-9, thin window GM detector, or equivalent	Portable survey meter for detecting beta radiation
Ludlum Model 19, MicroR meter, or equivalent	Internally-mounted 1x1 NaI gamma scintillator	Portable exposure rate survey meter for gamma radiation

3.2.10.2 Field Sampling Activities

Field sampling will consist of collecting representative samples of environmental media from sources for

either on-site measurements or off-site laboratory analysis. The following types of field samples will be collected:

- Black shale drill cuttings, accumulated solids, scale, treatment water sludge, discharge sediment, soil samples and crystalline salts from brine water evaporation as appropriate for off-site radiological laboratory analyses for characterization and evaluation of potential mobility in the environment;
- Flowback and produced water, for off-site radiological laboratory analysis for characterization purposes;
- Solid and aqueous phases to be evaluated separately;
- Swipe (smear) samples to determine removable alpha and beta surface contamination as an indicator of potential inhalation or incidental ingestion exposures.

3.2.10.3 Sampling Methods

Solid samples will be collected using reusable or disposable sampling tools (e.g., stainless steel trowels or tubes). Sampling tools will be decontaminated prior to first use on-site, between sampling locations, and following last use on-site (i.e., before demobilizing that equipment) as appropriate based on survey data. The samples selected for analysis will be placed into laboratory approved containers immediately following collection and labels promptly affixed to the sample containers. The samples will be transported via delivery service under chain-of-custody control to the off-site subcontract laboratory for analysis.

Representative samples will be collected for flowback and production water by performing multiple collection events over the entire flowback period and initial production. A representative grab sample will be collected from the appropriate tank/outlet using a disposable Teflon® bailer or a reusable stainless steel thief sampler; contents of the selected sampling implement will be added directly to sample containers. Samples will be placed into laboratory-prepared containers immediately following collection and caps and labels promptly affixed to the sample containers. In cases where sample valves are available, samples may be collected directly into approved sample containers. The samples will be transported under chain-of-custody control to the off-site subcontract laboratory.

3.2.10.4 Sampling Equipment Decontamination

Disposable sampling equipment will be used wherever possible to reduce decontamination requirements. When reusable equipment is used, such equipment will be decontaminated both prior to sampling in the field, between uses, and following the last use on each site, as appropriate. The following decontamination steps will be performed for reusable equipment, in the following order as necessary:

- 1) Potable water rinse;
- 2) Wash with laboratory-grade detergent (Alconox®, Liquinox® or equivalent);
- 3) Distilled water rinse;
- 4) Acetone, Isopropanol or Methanol rinse;
- 5) Distilled water rinse; and
- 6) Air drying.

3.3 Biological Hazards

The SSHO (or alternate SSHO) will also screen the area for biological hazards prior to beginning work. Care should be taken during field activities to prevent contact with biological hazards.

3.3.1 Insects

Ticks, bees, wasps, yellow jackets, black widow spiders, and brown recluse spiders present a potential hazard on this project. A victim suspected of being bitten by a black widow spider or brown recluse spider will receive medical attention. The venom from the brown recluse spider is capable of causing coma and kidney failure in its victim.

Protection against insects, such as protective clothing (Level D) and insect repellents (where necessary), will be used. Personnel will receive training on working in conditions where insects will be present prior to HVHHF activities.

3.3.2 Vermin

Feral cats, skunks, rats, mice, squirrels, and rabbits may be carriers of disease. Where vermin are identified in work areas, the SSHO (or alternate SSHO) shall be immediately notified. Bites will be immediately reported and medical care obtained.

Infections may occur in humans associated with activities that bring humans into contact with rodents, rodent saliva, or rodent excreta. Activities that may bring humans into contact with the etiologic agents causing infections include the following situations:

- Working in areas of field crops
- Disturbing rodent-infested areas
- Visiting areas where rodent populations have increased
- Entry into potential rodent-infested areas

Transmission of disease may occur through broken skin, contact with conjunctivae, ingestion of contaminated food or water, or inhalation of aerosols. Personal hygiene practices, such as frequent hand-washing, will help prevent rodent-borne diseases as well as using caution in areas likely to be occupied by vermin.

Workers will be advised that if a fever or respiratory illness develops within 45 days of the potential exposure, they should seek medical attention and inform the physician of potential Hantavirus exposure. All precautions will be made to ensure Hantavirus exposure is eliminated in the field. Rodent-borne diseases, including Hantavirus, result in severe respiratory distress and plague.

Section 4: Responsibilities

Woolsey's responsibilities and chain of command are discussed below.

4.1 Woolsey Responsibilities

Woolsey is responsible for taking all necessary precautions and providing the necessary protection to prevent damage, injury, or loss (as a result of project activities) to the following:

- All individuals at or near the location of the work performed
- All Woolsey employees and subcontractors
- All equipment or materials used in the work performed
- Other property at or adjacent to the site or work location

Woolsey will notify the project manager (PM) immediately when work may affect adjacent properties. Woolsey will obtain full compliance with this plan by its employees and subcontractors.

4.2 Chain of Command

Accountability for implementing and enforcing this SSHP lies with the CHSM. Day-to-day onsite accountability is delegated to the SSHO (or alternate SSHO). Each employee is responsible for

performing the tasks assigned to him/her in this SSHP. The individuals who fill these positions and the responsibilities assigned to them are detailed in Sections 4.2.1 and 4.2.2.

Subcontractor competent persons are also responsible for implementing and enforcing this SSHP.

4.2.1 Woolsey Corporate Health and Safety Manager

Mickey Neville from Basic's Pressure Service Division will act as the Corporate Safety and Health Manager (CSHM) on this project.

4.2.2 Site Safety and Health Officer

Tommy Marcellus will act as the Site Safety and Health Officer (SSHO) for this project.

Shane Herridge will act as an alternate SSHO for this project.

4.2.3 Public Visitors

Public Visitors who arrive on-site are responsible for following the Health, Safety and Environment policies of Woolsey (HSE) Management. Visitors are required to sign in immediately upon arrival and must be accompanied at all times while on-site with no exceptions. This policy allows site personnel to implement and maintain the HSE program and will periodically assess its effectiveness. On-site personnel who accompany visitors will ensure that safety programs are being followed, identify safety needs, communicate hazards, and supply and enforce the use of appropriate personal protective equipment and clothing. Employees, contractors, and visitors are expected to obey all safety rules, follow recommended procedures, use personal protective equipment and clothing, communicate hazards, and assist with ongoing improvements to Woolsey's HSE Management policies. Visitors and contractors who knowingly violate safety rules may face disciplinary action, dismissal and/or legal action.

Section 5: Health and Safety Training

Woolsey understands the importance of ensuring that employees and subcontractors are adequately trained to safely perform those tasks to which they are assigned during the HVVHF operations.

5.1 Site-Specific Health and Safety Training

Site-specific H&S training is presented to all employees as they are assigned to the site and periodically during the course of the project when there is a change in site activities. This onsite Field H&S Meeting will cover specific topics including: chemical and physical hazards associated with the task to be performed; necessary PPE required for the task; the type of environmental monitoring to be performed during the task; actions to be initiated based on environmental monitoring results; emergency and contingency plans; and task-specific topics such as small spill containment. Meeting attendance and materials covered are documented using the Field H&S Meeting Record in Attachment C.

No Woolsey employee or subcontractor will be put into a hazardous field situation without training. Prior to the initiation of HVVHF activities, all employees will attend a site-specific safety orientation given by the SSHO (or alternate SSHO) emphasizing the following:

- Names of personnel and alternates responsible for site H&S
- Site-specific H&S hazards
- Basic occupational H&S
- Appropriate PPE
- General occupational health
- Work practices by which employees can minimize risks from hazards
- Medical surveillance requirements, including recognition of symptoms and signs of exposure

- Onsite communication
- Evacuation routes
- Route to the hospital
- Emergency and fire response
- Smoking restrictions
- Locations of emergency equipment and list of emergency contacts
- Site work areas
- The SSHP

Topics covered in initial employee training are reinforced and emphasized in field orientation. It will include a tour of site facilities relevant to the HVHHF activities to be performed and the site safety equipment including the following (as appropriate):

- Fire extinguishers
- Eye wash stations
- Designated work areas
- First aid kits
- Posted emergency contact list

The contents of this SSHP shall be discussed among the entire field team prior to start of work. The field team shall simulate an emergency situation to exercise the guidance within this plan for emergency response procedures. The SSHO (or alternate SSHO) will evaluate the response, and provide feedback for lessons learned that will be incorporated into the existing site procedures.

5.2 Hazard Communication

OSHA Standard 29 CFR 1910.1200 "Hazard Communication Standard" requires that all employees handling or using materials that may be hazardous be advised and informed as to the hazard potential associated with those materials.

The SSHO (or alternate SSHO) will discuss with the team members the following items:

- An overview of the hazard communication requirement
- A review of the chemicals anticipated to be encountered during the course of project work
- The location and availability of the written hazard communication program and an inventory of chemicals expected to be encountered
- Methods and observation techniques that may be used to detect the presence or release of hazardous chemicals in the work area
- Procedures to lessen or prevent exposure to hazardous workplace chemicals
- Emergency procedures to follow if employees are exposed to hazardous chemicals
- Explanation of the proper use of PPE

5.3 Daily Health and Safety Meetings

The SSHO (or alternate SSHO) will conduct the daily H&S meetings for field workers. The SSHO (or alternate SSHO) will address safety concerns before the day's planned activities. The SSHO (or alternate SSHO) will discuss the meeting places in case of evacuation and rally points at this daily safety meeting,

as well as other H&S reminders regarding safe work practices discussed in this SSHP. These meetings will be documented in the field logbook. A brief meeting at the end of the day's work will also be attended by the field team if an emergency response situation has occurred.

5.4 Training Records

Initial employee, site-specific, and daily H&S training will be documented. The SSHO (or alternate SSHO) is responsible for documenting all training activities and maintaining the files. To ensure that all site employees have read and fully understand the contents of this SSHP, a signature form is provided as Attachment D.

Section 6: Personal Protective Equipment

For the protection of all persons involved with HVHMF operations on Woolsey projects, general application is required for the PPE described in this section. The SSHO (or alternate SSHO) will perform a hazard assessment requiring the use of PPE when developing a JSA for each Definable Feature of Work. Employees will review these PPE requirements during JSA review and at the safety meetings.

6.1.1 Eye Protection

Safety glasses shall be worn at all times except while in vehicles with enclosed cabs or where additional eye protection is required. Safety goggles in accordance with ANSI Z87.1 shall be worn when working with corrosive chemicals or when possible eye irritation hazards are present.

6.1.2 Hard Hats

Hard hats in accordance with ANSI Z89.1 shall be worn during all heavy equipment and HVHMF activities. No modification to the shell or suspension is allowed unless approved by the manufacturer in writing. Hard hats will be worn with the bill facing forward.

6.1.3 Shoes

Steel-toed boots are required. All foot gear must meet the requirements of ANSI Z41.1.

6.1.4 Shirts and Pants

The outer most layers must be fire resistant (FR) material and meet the NFPA 2112 standard.

6.1.5 Gloves

Personnel shall wear gloves that are appropriate for the hazard they require protection from.

6.1.6 Hearing Protection

Woolsey will implement a hearing protection program. This program will consist of performing an initial assessment that is designed to determine if persons in the defined work areas are exposed to sound levels greater than 85 dBA as a time-weighted average or 140 dBA impulses. Based on the initial assessment, the SSHO (or alternate SSHO) will make sure adequate protection is worn during those operations. If field conditions change, another assessment will be performed. This assessment will be based on task-based operations and will also focus on the work zone boundary.

6.1.7 Respiratory Protection

Woolsey has established a respiratory protection program for any employee that may be exposed to inhalation hazards while within the footprint of the wellsite. Any person required to wear a respirator on the job will receive instruction and training prior to using the equipment. In part, the training will include the nature, extent, and effects of the respiratory hazards to which a person may be exposed as well as signs and symptoms of exposure. Before a person is required to wear a respirator on the job, a

determination will be made that he/she is physically fit and able to wear a respirator. The respiratory protective program can be found in Attachment F of this SSHP.

6.1.8 Vehicle Safety

Seat belts shall be worn in all vehicles. Riding in the bed of pickups is prohibited. Vehicles will be inspected prior to each use. Only authorized Woolsey personnel and designated contractors are allowed to operate Woolsey vehicles used during the HVHMF operations.

6.1.9 Visitor Protection

All visitors to the well site will be provided with a hard hat, safety glasses, and hearing protection to ensure they are protected from potential hazard exposure while on the job site. Visitors will also be accompanied by site personnel while they are within the footprint of the operation to ensure they maintain a safe distance from any high hazard areas.

Section 7: Medical Surveillance

7.1 Purpose and Scope

All personnel performing onsite work that will result in exposure to contaminant-related H&S hazards shall be enrolled in a medical surveillance program that complies with OSHA standards 29 CFR (f) and 29 CFR 1926.65 (f).

Woolsey administers an occupational medical surveillance program for the following activities:

- Hazardous waste operations
- Activities that require the use of respiratory protection beyond the use of “loose fitting dust masks”
- Project-specific activities or job assignments that may expose employees to hazards where medical surveillance is required by regulation or it has been determined by the PM, resource manager and/or CHSM that a project-specific medical evaluation program or biological monitoring is warranted
- As requested by a client

The occupational medical surveillance program is designed and overseen by a board-certified occupational physician. The medical surveillance program is intended primarily to monitor an employee’s fitness for duty and is not intended for the diagnosis or treatment of injury or illness. The functions of the medical surveillance program include:

- Establishing a baseline medical condition prior to project or job assignment
- Monitoring the employee’s physical ability to perform assigned job functions
- Identifying the presence or absence of conditions that could be aggravated by the type of work assigned
- Monitoring health trends during hazardous waste and other designated project assignments
- Establishing a medical condition at time of termination or post assignment

In addition, medical exams or evaluations of employees may be provided in the following circumstances:

- Employment-related injuries or illnesses
- Exposures to toxic or hazardous substances
- Medical clearance to return to work

7.2 Responsibilities

Direct Managers and Resource Managers – Direct managers and resource managers ensure employees participate in the medical surveillance program when required by project assignment and notify the CHSM of employee termination or reassignment requiring an exit physical examination.

Corporate H&S Manager – The CHSM selects and monitors performance of the medical contractor and oversees Woolsey administration of the program.

H&S Coordinators – The H&S coordinator or their designees coordinate medical appointments and maintain employee medical clearance forms for their office(s).

Medical Consultant – The medical surveillance consultant identifies qualified clinics, medical facilities, and maintains employee medical records. The medical consultant provides the services of a board certified occupational physician to advise on recommended medical protocols, provide medical opinions regarding employee fitness for duty, and provide medical advice as requested.

Employees – Employees selected for activities that include participation in a medical surveillance program are responsible for participating in the program by attending assigned appointments and maintaining their medical qualifications.

7.3 Medical Release Forms

Upon completion of a medical exam or evaluation, results shall be reviewed by the medical consultant's occupational physician and a medical release letter shall be sent to the H&S database administrator indicating the medical status of the employee. The medical consultant shall also provide a copy of the results of the exam to the employee.

7.4 Employment-Related Injury or Illness Medical Evaluations

In a non-emergency situation, employees who are injured or contract an illness that may be related to their employment at Woolsey should notify their direct manager or resource manager and contact their CHSM or H&S coordinator. If necessary, an appointment will be arranged at a medical facility identified by the medical consultant at a time and location convenient to the employee.

The CHSM or H&S coordinator must be notified by the employee, their group leader, direct manager, or resource manager prior to seeking non-emergency medical services for employment-related injuries or illnesses.

7.5 Return to Work Examinations

An employee desiring to return to work following a leave of absence due to injury or illness, or return to full work status from a restricted work period, must obtain a medical release to work, signed by a licensed physician stating that the employee is capable of performing assigned duties with or without restrictions and with or without reasonable accommodation. The content of the examination may be determined by the medical consultant and may be performed at a facility selected by the medical consultant at a time and location acceptable to the employee. A medical work status form should be provided to the CHSM and human resources benefits manager.

7.6 Access to Medical Records and Exposure Data

Employee medical records, including results of medical tests and X-Rays, shall be retained by the medical consultant and kept confidential in accordance with OSHA medical record-keeping requirements, 29 CFR 1910.1020. Medical records, and information obtained in the course of the administration of the Woolsey medical surveillance program shall be kept confidential and released only under the following conditions:

- An employee, former employee, or their designated representative may obtain a copy of his/her personal records by submitting a written request for the information to the CHSM. The written

request must include the employee's name, the address to send the records to, and a phone number to call to verify the identity of the requestor.

- Woolsey's workers' compensation insurance carrier may request information related to alleged occupational illnesses or injuries with the written permission of the employee.
- The CHSM may obtain medical information without personal identifiers by submitting a written request to the medical consultant.
- Recognized government research and regulatory agencies may obtain medical information without personal identifiers by submitting a written request to the CHSM. The request shall identify the nature and purpose of the information requested.

Air monitoring data and exposure records for specific projects are kept with project H&S records. Employees may obtain access to data related to their exposure or generic data associated with potential exposure of employees in their job classification or performing similar duties by submitting a written request to their CHSM.

Section 8: Air Monitoring

Refer to the Fugitive Dust Control Plan for air monitoring requirements. All personnel will wear personal monitors while working on location.

Section 9: Heat and Cold Stress Prevention

Seasonal site conditions should be considered for all HVHHF activities. Heat and cold stress prevention will be practiced in accordance with the techniques in the following sections and in Attachment B of this SSHP.

9.1 Heat Stress Prevention

Heat stress occurs when the body's physiological processes fail to maintain a normal body temperature because of excessive heat. Individual susceptibility to heat stress disorders can vary widely. Individual physical factors that can affect a person's response to hot work environments include a person's general fitness and age. If necessary, appropriate heat stress prevention can include the following techniques:

- Advise workers to drink 16-ounces of water before beginning HVHHF activities and continue to drink fluids throughout the work day.
- Acclimatize workers to site work conditions by slowly increasing workloads.
- Wear loose clothing, appropriate to the weather and HVHHF tasks.
- In hot weather, conduct HVHHF activities in the early morning and evening.
- Allow appropriate rest period (i.e., at least 15 minutes each hour, depending on working and weather conditions).
- Ensure that adequate shelter is available to protect personnel against heat.

Attachment B to this SSHP, Heat and Cold Stress Guidelines, contains more information regarding heat stress monitoring.

9.2 Cold Stress Prevention

Factors that contribute to cold stress exposure include temperature, humidity, wind, sunlight, rain, snow, fog, exposure duration, clothing, and work activity. Cold Stress is not a major concern since colder temperatures are not expected during field activities. If necessary, the following prevention techniques should be considered when working in ambient air temperatures below 40 degrees Fahrenheit (°F),

especially when other contributing weather conditions such as snow, rain, or wind are present.

- Employees whose clothing may become wet shall wear an outer layer of clothing that is impermeable to water.
- Dress in layers and bring extra clothing.
- When manual dexterity is not required of an employee, thermally protective gloves shall be worn.
- Curtail work if extreme weather conditions such as a blizzard, extreme wind chill (e.g., less than 0°F), torrential cold rains, or wind is expected.
- Take warming breaks as needed.

Attachment B to this SSHP, Heat and Cold Stress Guidelines, contains more information regarding heat stress monitoring.

Section 10: Standard Work Practices

Standard work practices have been developed for general as well as for specific task activities. Some minimum standard general work practices are outlined below.

10.1 General HVVHF Activities

Specific safety practices associated with equipment and HVVHF activities conducted during work activities are listed in the JSAs; general safety practices include:

- Qualified, adequately trained, and licensed personnel will be onsite.
- Personnel will not consume or be under the influence of alcoholic beverages, medication, or drugs while operating heavy equipment. The presence of intoxicating substances on site is strictly prohibited.
- Work area will be kept clear of obstructions and debris.
- Personnel will wear proper PPE during all activities

10.2 Working around Heavy Equipment

Heavy equipment will be used on the jobsite. All heavy equipment shall be operated only by qualified (by training and experience) personnel who are authorized to operate the equipment to be used onsite.

- Assume the operator cannot see you. The operator's vision may be blocked by blind spots. He or she is frequently concentrating on their work and equipment and may not notice a site visitor.
- If you must approach the operator, be sure you have made eye contact with the operator and they know you will be approaching them before approaching the equipment. Verbal contact, direct or by radio, is even better. Do not approach if the equipment is moving or in operation.
- Stay clear of pinch points and swing areas of equipment. At Woolsey projects, these areas should be taped or barricaded off, however, when equipment moves frequently, you cannot count on the other organizations to mark these zones.
- Do not walk near a moving piece of equipment. It could turn or rotate any minute. Modern construction equipment moves fast and in any direction.
- On a noisy site, you may not notice the equipment's' backup alarm. Keep aware of what is happening around you.
- Never walk under a load on a crane or hoist.
- Do not cut across the path of equipment backing up.

- Wear your hardhat and safety glasses. The safety glasses protect your eyes from dust and debris and the hardhat provides protection for your head and makes you more visible on the site.
- On sites where there is frequent vehicle or construction equipment movement, wear high-visibility clothing.
- Maintain a clearance of a least 10 feet between any part of the machine or its load and electrical line or apparatus carrying up to 50,000 V. One foot of additional clearance is required for every additional 30,000 V.

10.3 Underground Utilities

Some tasks milestones in this SSHP may require drilling or heavy equipment penetrating the ground. In all these tasks utilities located underground will be a concern and hazard. Utility mark outs and geophysical contractors will be procured to locate any potential underground utilities in all work areas prior to any work completed in each milestone.

10.4 Spill Response

In the event that a spill occurs, the following procedures will be taken:

- The spill will have absorbent material placed over the area. Enough absorbent will be used to contain the entire spill. The absorbent material will then be placed in an appropriately labeled container using a shovel and disposed of properly.
- PPE to be used during the spill cleanup will be equal to the PPE being worn when the spill occurred, unless the SSHO (or alternate SSHO) determines that a PPE upgrade is necessary.
- The spill will be reported to the Woolsey PM and noted in the field logbook.

The spill response equipment will be stored in the OCV.

10.5 Site Safety Practices

Historically, slips, trips, and falls have been major causes of physical injuries. To prevent this type of hazard, tools, parts, and other equipment should not be left lying around. Grease and oils found on the ground should be cleaned up as soon as possible. The simple knowledge of proper lifting techniques, bending the knees and lifting with muscles of the legs can eliminate many strained or injured backs.

Several general practices will be followed to ensure personnel safety during operations at the site. The following is a list of some of these practices:

- Do not run on location.
- Do not operate moving equipment unless instruction in its use has been given and use authorized by the SSHO (or alternate SSHO).
- Observe driving regulations within the site. These include wearing seat belts at all times when the vehicle is in motion and maintaining posted speeds or under 10 miles per hour.
- Get authorization from the SSHO (or alternate SSHO) before removing safety equipment or supplies from their normal location.
- Clean hand tools and special tools and keep them in good repair.
- Use the correct tool for the particular job in the proper manner.
- Carry materials and tools with concern for overloads and balance, and hold these items securely.
- Avoid movement with obscured vision.
- Practice good housekeeping at all times.

- Do not participate in "horseplay". Horseplay is defined as any frivolous behavior that increases the probability of an accident.

10.6 Material Lifting

Many types of objects may be handled during the course of HVHHF activities. Care should be taken in handling heavy or bulky items, because they are the cause of a considerable number of accidents. There are certain fundamentals in the proper lifting of materials to avoid back injuries as listed below:

- The size, shape, and weight of the object to be lifted must be considered. A worker will not lift more than what one person can handle comfortably.
- The feet will be placed far enough apart for good balance and stability. The footing will be solid.
- The worker will get as close to the load as possible. The legs will be bent at the knees. If the load is too large or bulky and the worker cannot see around or over it, the worker will get assistance.
- The back will be kept as straight as possible.
- The object will be gripped firmly.
- To lift the object, the legs are straightened from their bend. Twisting motions will be avoided while lifting and/or carrying objects.
- A worker will never carry a load that cannot be seen over or around.
- When placing an object down, the stance and position are identical to that for lifting. The legs are bent at the knees and the object lowered.

When two or more workers are required to handle an object, coordination is essential to ensure that the load is lifted uniformly and that the weight is equally divided between the persons carrying the load. When carrying the object, each worker, if possible, will face the direction in which the object is being carried. In handling bulky or heavy items, the following guidelines will be followed to avoid injury to the hands and fingers:

- A firm grip on the object is essential. The hands and object will be free of oil, grease, or water that might prevent a firm grip.
- The item will be inspected for metal slivers, jagged edges, burrs, and rough or slippery surfaces.
- Gloves will be used when necessary.
- The fingers will be kept away from any points that may cause the fingers to be pinched or crushed, especially when setting the object down.

10.7 Contingency Plans

If unexpected hazards or conditions are encountered, field personnel will stop work and move a safe distance from the site, upwind or to the access road. Work stoppage will continue until the SSHO (or alternate SSHO) indicates it is safe to return to the site.

If unsafe conditions persist, the SSHO (or alternate SSHO) will notify Woolsey's PM, and the Woolsey CHSM will be notified by the PM, as needed.

Section 11: Site Control and Personal Hygiene

The following site control and personal hygiene activities will be followed:

- All personnel and general public will be required to sign in and out of the location for accountability purposes and to ensure that unauthorized access to the site is not granted.
- Signs will be posted at the entrance to the location to distinguish the wellsite to the general public,

so that they will know that there are additional hazards associated with the locations footprint.

- All Woolsey and subcontractor personnel assigned to work in any restricted area must be provided with a copy of this SSHP, agree to the terms in writing and sign the form in Attachment D, and attend a safety briefing before commencing work.
- All team members will make sure to address personal hygiene issues by washing hands, arms, and face prior to eating, drinking, smoking, applying lipstick, or any other hand to mouth function.
- Eating, drinking, and chewing gum, or tobacco will only be permitted outside the work zone. Smoking is permitted in designated areas only.
- Before initiating any non-routine operation, personnel must consult the SSHO (or alternate SSHO) about H&S requirements for that operation.

Section 12: Accident and Illness Prevention

12.1 Introduction

Woolsey believes that the H&S of each of its employees is of the utmost importance. Woolsey's objective is a HSP that reduces the number of illnesses and injuries to an absolute minimum. The Woolsey medical surveillance program, designed and administered by a board-certified, occupational physician, consists of a combination of (1) baseline, annual, interim, exit, and return to work examinations; (2) services for the evaluation and follow-up of occupationally-related injuries and illnesses; and (3) emergency medical services required to stabilize severely injured or ill patients prior to their transport to an offsite medical care facility. The prevention of occupationally induced illnesses and injuries takes precedence over operating productivity at all times. Woolsey provides quality supervision, training and educational opportunities, and protective clothing and equipment to ensure maximum employee H&S protection. Subcontractors will provide training and educational opportunities, and protective clothing and equipment for subcontractor employees to ensure H&S protection of its employees.

12.2 Safety Promotion

The training and subsequent implementation of the HSP, as well as the scheduled site-specific training, are all designed to instill a high level of safety consciousness in all personnel working on the project. These programs, in conjunction with the high level of experience and professionalism of the personnel working onsite and the periodic safety audits and inspections, will maintain safety as a prime concern for all involved. Additionally, the performance of work in a safe manner is expected and required from each Woolsey employee and subcontractor.

12.3 Medical and First Aid Requirements

Notification of, and arrangement with medical facilities, ambulance service, and medical personnel will be established to ensure their readiness and availability for prompt attention to the injured prior to implementation of HVVHF activities. The list of emergency contacts is included in Table 13-1. A minimum of two Woolsey or subcontractor employees performing HVVHF activities for this project will have current First Aid/CPR training certificates.

At least one first aid kit will be maintained onsite during field operations. These kits will have been reviewed by a medical consultant for their adequacy. The first aid kit will be stored in the OCV.

Section 13: Emergency Response and Contingency Procedures

If field personnel observe a potential or actual emergency condition, such as a chemical spill or fire, they will notify the personnel listed in Table 13-1. In the case of an emergency such as a fire at an off-site location, the appropriate agencies (i.e., the fire department [911]) will be notified. During the morning

H&S briefing, the emergency action plan will be discussed and demonstrated. The contents of this SSHP shall be discussed among the entire field team prior to start of work. The field team shall simulate an emergency to exercise the guidance within this plan for emergency response procedures. The SSHO (or alternate SSHO) will evaluate the response, and provide feedback for lessons learned that will be incorporated into the existing site procedures.

The emergency alerting procedure will be a 5-second continuous sounding of the field vehicle's horn. All posted safety and health requirements onsite will be strictly followed. If unexpected hazards or conditions occur, field personnel will evacuate immediately and meet upwind of the site at the meeting place designated during the field kickoff meeting. It will be the responsibility of the SSHO (or alternate SSHO) to account for all field personnel that have evacuated the site. Field personnel will be instructed to contact the SSHO/alternate SSHO via cell phone if they evacuate the site to somewhere other than the agreed upon safe meeting location. The proper authorities listed in Table 13-1 will be contacted.

13.1 Emergency Medical Facility

The medical facility used for emergencies related to HVVHF activities conducted is:

Hamilton Memorial Hospital
611 S. Marshall Ave.
McLeansboro, Illinois 62859

Directions to Hospital from worksite:

Head north on County Road 50E toward County Road 1825N – 0.06 mi
Turn right at the first cross street onto County Road 1825N – 1.5 mi
Turn right onto US-45S – 4.2 mi
Turn right onto IL-14W – 11.2 mi
Turn left onto S. Marshall Avenue – 0.2 mi

13.2 Medical Emergencies

In the event of an accident requiring first aid, the SSHO (or alternate SSHO) will be responsible for coordinating the first aid and/or requesting aid from a medical service (Table 13-1). If the person requiring attention is capable of being moved without further injury, the SSHO (or alternate SSHO) may transport the injured party to obtain medical assistance. Site support vehicles may be used to transport injured or ill personnel. Directions and maps showing the routes to the medical facility will be located in all vehicles. This SSHP should also be brought to the hospital. As aforementioned, a minimum of two Woolsey or subcontractor employees performing field activities for this project will have current CPR and first aid training certifications.

Depending on the seriousness of the injury, treatment may be given at the site by trained response personnel. Emergency first aid equipment, such as a first aid kit, will be in the OCV on site. For more serious injuries, additional assistance may be required at the site, or the victim may have to be treated at a medical facility. Any members of the general public, who incur any injury while within the footprint of the project, will be treated in the same manner as those working on the job site.

Life-saving care should be instituted immediately without considering decontamination, if chemical exposure occurs. The outside garments can be removed (depending on the weather) if they do not cause delays, interfere with treatment, or aggravate the problem. If the other contaminated garments cannot be safely removed, the individual should be wrapped in plastic, rubber, or blankets to help prevent contaminating the inside of the ambulance and/or medical personnel. Outside garments will then be removed at the medical facility. No attempt should be made to wash or rinse the victim. One exception would be if it is known that the individual has been contaminated with an extremely toxic or corrosive material that could also cause further or severe injury or loss of life. For minor medical problems or injuries, the normal decontamination procedure should be followed.

Exposure to chemicals can be divided into two categories:

1. Injuries from direct contact such as acid burns or inhalation of toxic chemicals
2. Potential injury due to gross contamination on clothing or equipment

If a contaminant is inhaled, treatment can only be conducted by qualified physicians. If the contaminant is on the skin or in the eyes, immediate measures must be taken to counteract the substance's effect.

When protective clothing is grossly contaminated, contaminants may be transferred to treatment personnel or the wearer and cause injuries. Unless severe medical problems have occurred simultaneously with splashes, the protective clothing should be washed off as rapidly as possible and carefully removed. Workers showing symptoms of acute exposure should be transported, immediately, following appropriate decontamination, to the nearest medical facility.

Heat-related illnesses range from heat fatigue to heat stroke, the most serious condition. Heat stroke requires prompt treatment to prevent irreversible damage or death. Protective clothing may have to be cut off. Less serious forms of heat stress require prompt attention or they may lead to a heat stroke. Section 9 and Attachment B present a discussion of recommended heat stress prevention procedures. Any worker who is medically treated for a heat stress related injury will be evaluated by a physician and medically cleared before return to work.

13.3 Exposure/Injury Reporting

The purpose of the exposure/injury reporting system is twofold: (1) to learn from past mistakes in order to maintain an exposure/injury-free work environment and (2) to document incidents as required by OSHA. The reporting system consists of monthly surveys and exposure/incident reports. All incidents involving injury, illness, exposure, vehicle, or equipment damage will be thoroughly investigated by the CHSM, including incidents that might not cause injury, illness, or property damage but had the potential to do so ("near miss incidents").

13.3.1 Accident Reporting and Investigation

Personnel are required to notify the CHSM of reportable exposures and injuries. Individuals will discuss all potential exposures with the CHSM and/or SSHO/alternate SSHO to ascertain if the exposure is reportable. All injuries will be reported.

An Injury/Illness Report Form will serve as the basis for the written documentation and investigation of all accidents resulting in employees receiving more than first aid. All such accidents will be verbally communicated to the CHSM or SSHO/alternate SSHO as soon as medical services are secured. These individuals will verbally notify the CHSM within 24 hours of the accident.

The investigation will be thorough and performed by the injured employee's immediate supervisor. The results of the investigation will be documented using the report form and will be signed by the investigator. The form will then be sent to the appropriate section or local manager, who following a review is also required to sign the form before forwarding it to the SSHO (or alternate SSHO). Following the SSHO/alternate SSHO's review and signature, a copy of the form will be made for the office/project file with the original forwarded to the CHSM.

13.3.2 Follow-Up

If the injury/illness resulted from the uncontrolled release of hazardous material, the CHSM will be notified immediately, so that discussions with the occupational physician can occur to determine if additional biological monitoring should be prescribed.

As soon as practical, following the initial medical treatment, the injured employee will be scheduled into the clinic that administers the annual examinations for the injured employee's office. This procedure is

necessary to ensure that the employee receives quality medical treatment during any type of recovery period.

The CHSM and the SSHO/alternate SSHO will follow up with the PM to ensure that corrective action, if identified in the Injury/Illness Report Form, has been implemented.

13.3.3 Occupational Injuries and Illnesses

The CHSM maintains a log of all occupational injuries and illnesses in accordance with OSHA requirements. The log is maintained using OSHA Form 200.

13.4 Emergency Evacuation Plan

The following steps are to be taken in the event that evacuation of the general public in close proximity of the well site becomes necessary due to a fire, explosion, or spill.

1. In the event that there is a problem at the well site which poses a threat to the general public, the SSHO will notify the Sheriff's Department. If the SSHO is incapacitated the site supervisor will make the proper notification.
2. Once the Sheriff's Department has been notified of the emergency, they will contact additional resources dependent upon the type of emergency.
3. If isolation and evacuation are necessary, the Sheriff's Department will dispatch units to set up roadblocks and assist with the evacuation.
4. The project manager will begin the evacuation of those in immediate danger, based on wind conditions at the site. They will begin by telephoning any residents in the danger zone directly downwind from the location in the potential radius for exposure. They will then proceed to the residents whom they were not able to contact by phone to make a face-to-face contact to insure that they have evacuated.
5. The entrance to the location will be blocked off and any incoming vehicles will be diverted away from the wellsite. Only emergency response and authorized vehicles will be granted entrance to the location.
6. In the event that it becomes necessary to divert school busses away from the wellsite, the project manager, or their designee, will notify the local school district.
7. Onsite personnel will take every step within the means of their training to mitigate or eliminate the emergency situation and begin to establish a safe perimeter.
8. The Illinois Department of Natural Resources (IDNR) and any other appropriate government officials will be notified of the emergency situation.
9. Other contractors may be called upon to assist in the elimination and cleanup from the emergency situation.

13.5 Fire or Explosion Response Procedures

The objective of this Emergency Response Procedure is to identify the appropriate actions to take in the event of a fire or explosion at the wellsite location.

1. If you observe a fire and/or explosion on or near the location, contact personnel in the OCV and sound the alarm. Give specific directions to the area affected by the fire or explosion. Provide the OCV with sufficient information to determine what response actions and resources are necessary.
2. If a fire or explosion is ongoing, the OCV will immediately call 911 (fire department) and provide the dispatcher with the following information
 - a. Location of the fire
 - b. Time the fire started or the explosion occurred
 - c. Number of personnel on the site at the time of the incident
 - d. Any chemicals which may be involved in the fire or explosion

- e. Any other pertinent information the dispatcher may ask for
3. The OCV shall then notify and direct the First Responders to the scene. Depending on the severity of the fire or explosion, the Responder(s) should wait at a safe distance to direct other responders or implement evacuation of the area, if necessary.
4. The OCV shall monitor the location entrance to direct any emergency vehicles to the scene. If possible, an employee will be at the gates to escort responders to the scene.
5. The First Responders shall evaluate the fire/explosion to determine the following:
 - a. Location of the fire/explosion
 - b. Type of material(s) that are burning
 - c. Potential spread or exposure
 - d. Fire protection systems activated
 - e. Site evacuation necessary or on-going
 - f. Other potential safety or environmental hazards
6. The evaluation information can be relayed by the First Responders either upon the fire department arrival on-scene or through continuous contact through the dispatcher
7. If Responder(s) determine that the fire is already extinguished or will be extinguished immediately using on-site resources (incipient stage fires only), the Incident Commander can cancel fire department prior to its arrival.
8. If the potential for encounter with smoke or an Immediate Dangerous to Life and Health (IDLH) atmosphere exists, prior to entry, the First Responders may don self-contained breathing apparatus (SCBA). SCBA shall only be worn by personnel trained and medically cleared for its use. Upon encountering smoke or a potential IDLH environment, First Responders shall immediately activate their SCBA unit and exit the area. The First Responders shall not use SCBA for any firefighting or search and rescue purposes, but rather solely for respiratory protection during egress. All firefighting beyond the incipient stage, and all personnel search and rescue shall be performed by the fire department.
9. Responder(s) shall ensure that any affected electrical systems are shut down along with any affected operations, if it is safe to do so.
10. The OCV will notify the First Responder(s) of the arrival of the fire department. The First Responder(s) will report to the location entrance, if necessary, and coordinate with the fire department in establishing an on-scene mobile command post to direct fire or explosion responders. They will direct individuals to assemble at the command post to help coordinate response efforts, verify that the appropriate fire or explosion response personnel have responded to the incident, and obtain additional back-up, if necessary.
11. All First Responders will assist the fire department as necessary and as directed (if the activities can be conducted in a safe manner) by the Incident Commander with:
 - a. Connections to water sources.
 - b. Identification of materials involved.
 - c. Use of proper personal protective clothing.
 - d. Isolation of electrical systems
 - e. Identification of fire suppression systems
12. Responders will identify any hazardous substances that may have been involved in the fire or explosion. SDS may be obtained from the electronic database, or if necessary and safely obtainable, hard copies in the OCV respectively. Responders shall also refer to the U.S. Department of Transportation Guidebook for First Response to Hazardous Materials Incidents for Emergency Actions for Small and Large Fires. The Responder(s) shall implement the wellsite spill response plan, as needed, to address a spill of oil or hazardous material associated with the fire or to initiate cleanup activities.

13. The Responder(s) will evaluate the need for medical services and perform rescue operations. Refer to the medical procedures and evacuation procedures.
14. The Incident Commander will assess actions needed to mitigate on-site and off-site impacts and environmental impacts.
15. The Incident Commander will determine when the emergency is over and provide the “all clear” announcement.
16. After the emergency has been terminated, the Incident Commander shall coordinate a debriefing and emergency documentation. Other activities to be considered/conducted following termination of the incident shall include:
 - a. Briefing Public Relations so that all questions can be directed to them
 - b. Coordinate the refilling of any fire extinguisher which may have been used
 - c. Forming a team to clean up the affected area to resume normal operations
 - d. Conducting an incident investigation
 - e. Analyzing the fire/explosion emergency response plan for its effectiveness

13.6 Spill Response Procedures

Significant spillage of certain types of materials that are at the facility may need to be reported to agencies such as Illinois Department of Natural Resources (IDNR), Environmental Protection Agency (EPA), etc. Substantial fines can result from improper or unauthorized handling of spills, as well as from not reporting them to the proper agencies.

The objective of this Emergency Response Procedure is to identify the appropriate actions to take when a spill or release of oil, hazardous materials or other potentially harmful substances (i.e., sanitary waste, blood, etc.) occurs at the wellsite location. The intent is to minimize the health, safety and environmental impacts from a discharge of fuel, lubricating oil, or hazardous material and to prevent discharge(s) from leaving the site, especially to the nearby waterways. Response activities will be completed only when it is determined to be safe to do so.

A spill is defined as a release of a material from outside its normal container. Spilled materials can be liquid, solid, or gas in nature. Because fires also release chemicals (smoke, fumes, etc.), they fall into the definition of a spill and therefore, also need to be reported internally. Releases into spill containment areas (dikes, separators, etc.) are still considered spills, must be reported internally, and may need to be reported to governmental agencies depending upon the type and quantity of material released.

- a. Immediate notification shall be given by the owner/operator of the wellsite location when a release equal to or exceeding the reportable quantity of an extremely hazardous substance or a CERCLA hazardous substance is released at the wellsite location. Notification will be provided to the following:
 1. Illinois Emergency Management Agency (IEMA)/State Emergency Response Commission (SERC) at 1-800-782-7860
 2. The Local Emergency Planning Committee for Hamilton County (Mr. William Sandusky) at 1-618-231-4001
 3. The National Response Center (NRC) at 1-800-424-8802 (if the substance meets the criteria of a CERCLA hazardous substance.
- b. Immediate notification must also be given if the hazardous substance release results in any of the following:
 1. A member of the general public is killed
 2. A member of the general public receives injuries resulting in hospitalization
 3. An authorized official of an emergency agency recommends an evacuation of an area by the general public
 4. Fire, breakage, release or suspected contamination occurs involving an infectious agent

5. Any release of petroleum (or oil) that produces a sheen on nearby surface water⁴ and/or threatens navigable waters
- c. Notification shall include the following criteria:
1. The chemical name or identity of any substance involved in the release
 2. An indication of whether the substance is an extremely hazardous substance
 3. An estimate of the quantity in pounds of any such substance that was released into the environment
 4. The time and duration of the release
 5. The specific location of the release
 6. The medium or media (air, land, water) into which the release occurred
 7. Any known or anticipated acute or chronic health risks associated with the emergency and, where appropriate, advice regarding medical attention necessary for exposed individuals
 8. Proper precautions to take as a result of the release, including evacuations
 9. The name and telephone number of the person or persons to be contacted for further information.
- d. Written follow-up notice is required with respect to incidents as described above, according to the IEMA. As soon as practicable after such release (within 30 days), the owner or operator shall provide a written follow-up emergency notice (or notices, as more information becomes available) to the SERC and the LEPC, updating the information provided in the immediate notification and including additional information with respect to:
1. Actions taken to respond to and contain the release
 2. Any known acute or chronic health effects associated with the released substance
 3. Advice regarding medical attention necessary for exposed individuals

13.6.1 Spill Response

1. If you detect a spill at the wellsite location:
 - a. Immediately contact the OCV. Provide information regarding the nature and extent of the spill so that they can initiate appropriate response activities. This information shall include:
 - Type of chemical spilled
 - Location of the spill
 - Approximate volume of the spill
 - Number of injured employees; and
 - If possible, a copy of the SDS for the spilled chemical.
 - b. Determine if the spill is significant by estimating the volume of spilled material.
 - c. If the spill is not significant, operations must clean up the spill immediately. For non-significant spill cleanup procedures, refer to the SDS or contact the SSHO. Notify your supervisor and/or the SSHO following clean up.
2. If you detect a spill that is in progress, initiate actions to stop or control the spill, if it is safe to do so and you are adequately trained and authorized to do so. Your supervisor should be informed of the spill as soon as conditions permit.
3. Based on the information provided, Operations will notify the First Responders and direct them to the scene. Operations may also notify additional response personnel, including the emergency coordinator (for significant spills), fire department (in case of fire/explosion, the waste contractor, and/or off-site resources) as directed by the Incident Commander.
4. Upon arrival at the scene, the Responder(s) shall

- a. Assess the spill event and secure access to the affected area. Depending on the type or quantity spilled.
 - b. Determine if any injuries are involved, and if so, will implement or direct someone else to implement the Medical Emergency Procedure.
 - c. Determine if evacuation is necessary and if so, will implement or direct someone to implement the Evacuation Procedure.
 - d. Determine if a fire/explosion hazard exists and if so, will implement or direct someone to implement the Fire/Explosion.
5. The Responder(s) should cordon off and secure the spill area, at a safe distance and should secure any affected operating equipment and possible ignition sources or other hazards.
 6. The Incident Commander should designate support, decontamination and hot zones as necessary.
 7. If the release has impacted or may potentially impact the surrounding waterways, the Responder(s), under the direction of the Incident Commander, should secure access to the affected area, which may include:
 - a. Request the Control Van to notify the Emergency Spill Responders
 - b. Securing skimmers and/or booms near openings to those waterways
 8. If a potential Reportable Quantity (RQ) has been released, the Incident Commander will request the OCV to notify the SSHO to assist in the evaluation of the spill/release to determine whether the release potentially triggers any reporting criteria.
 9. Following the completion of spill response activities, the Incident Commander should contact the SSHO to arrange for the storage and disposal of waste generated during spill response. Types of solid materials that may need to be disposed of include sorbent pads, protective clothing, and soil impacted by the release. Liquids would include water, oil, and chemicals recovered as part of the spill response activity, as well as fluids used for decontamination processes.
 10. Soils that are excavated must be transported to a secure location at a designated soil stockpile area, where they must be segregated, placed on plastic sheeting, covered, and labeled pending characterization and disposal. Other solid waste, slurry, sediment, and liquid waste must be containerized in drums or tanks and labeled with sufficient information to enable subsequent tracking and disposal. The EHS department must be notified of the quantities, nature, and date of generation of all waste products, and is responsible for arranging for classification and recycling, re-use, or disposal in accordance with State and Federal regulations.
 11. After the spill/release incident has been stabilized or remediated, the Incident Commander shall conduct a debriefing/critique of the spill/release ERP.

13.7 Equipment and Training


The well site is located in White County and this area has for decades experienced oil production, field service, drilling and completion activity. The White County Emergency Management Agency has the training and equipment for oil field related fires, including foam trucks. Emergency spill contractors have been identified in Table 13-1. The Mt. Vernon, Illinois Fire Department has 2 Hazmat Trucks and Trailers with Hazmat equipment.


Table 13-1 Emergency Contacts

Resource	Provider/Title	Telephone No.
Emergency Contacts		

Fire Department	Enfield Fire Protection District	911
Ambulance Service	White County Ambulance Service	911
Hospital	Hamilton Memorial Hospital	(618) 643-2361
Poison Control Center		(800) 222-1222
Woolsey Operating Company		
Ryan Kelley	Project Manager	[REDACTED]
Mickey Neville	CHSM	[REDACTED]
Tommy Marcellus	SSHO	[REDACTED]
Woolsey – Wichita, Kansas	Main Number	[REDACTED]
Emergency Spill Contractors		
Bodine Environmental Services, Inc.	Decatur, IL	(217) 428-3629
	Springfield, IL	(217) 698-0700
SET Environmental, Inc.	Glenwood, IL	(847) 537-9221
SWS Environmental Services	Paducah, KY	(270) 444-8003

Figure 13-1 Map to Emergency Medical Facility





Attachment A

Safety Data Sheets

SAFETY DATA SHEET

M34514 NA_EN



Occidental Chemical Corporation

A subsidiary of Occidental Petroleum Corporation



HYDROCHLORIC ACID (HCl) (ALL GRADES)

MSDS No.: M34514

Rev. Date: 09-Aug-2012

Rev. Num. 06

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Company Identification: Occidental Chemical Corporation
5005 LBJ Freeway
P.O. Box 809050
Dallas, TX 75380-9050

24 Hour Emergency Telephone Number: 1-800-733-3665 or 1-972-404-3228 (U.S.); CHEMTREC (U.S.): 1-800-424-9300; CHEMTREC (outside U.S.): +1 703-527-3887

To Request an SDS: MSDS@oxy.com or 1-972-404-3245

Customer Service: 1-800-752-5151 or 1-972-404-3700

Trade Name: Hydrochloric Acid (HCl) aqueous all grades

Synonyms: Muriatic Acid, HCl Solution, Aqueous hydrogen chloride

Product Use: Process chemical, Metal cleaning, Water purification, Petroleum Industry

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

Color: Colorless

Physical State: Liquid

Appearance: Clear

Odor: Irritating, Pungent, Sharp

Signal Word: Danger

HYDROCHLORIC ACID (HCl) (ALL GRADES)

M34514 NA_EN
MSDS No.: M34514

Rev. Date: 09-Aug-2012

Rev. Num. 06

MAJOR HEALTH HAZARDS: CAUSES BURNS TO THE RESPIRATORY TRACT, SKIN AND EYES. CAUSES PERMANENT EYE DAMAGE. DO NOT GET IN EYES, ON SKIN, OR ON CLOTHING.

PHYSICAL HAZARDS: May spatter or generate heat when mixed with water. Contact with metals may evolve flammable hydrogen gas.

PRECAUTIONARY STATEMENTS: Do not breathe vapor or mist. Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Wash thoroughly after handling. Use only with adequate ventilation.

POTENTIAL HEALTH EFFECTS:

Inhalation: May cause irritation (possibly severe), chemical burns, and pulmonary edema.

Skin contact: May cause irritation (possibly severe) and chemical burns.

Eye contact: May cause irritation (possibly severe), chemical burns, eye damage, and blindness.

Ingestion: Not a likely route of exposure.

Chronic Effects: Repeated or prolonged exposure to dilute solutions may result in dermatitis. Discoloration of the teeth may occur as a result of long term exposure.

Interaction with Other Chemicals Which Enhance Toxicity: None known.

Medical Conditions Aggravated by Exposure: None known.

See Section 11: TOXICOLOGICAL INFORMATION

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Component	%	CAS Number
Hydrogen chloride	9 - 36	7647-01-0
Water	63 - 91	7732-18-5

4. FIRST AID MEASURES

INHALATION: If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. If respiration or pulse has stopped, have a trained person administer basic life support (Cardio-Pulmonary Resuscitation and/or Automatic External Defibrillator) and CALL FOR EMERGENCY SERVICES IMMEDIATELY.

SKIN CONTACT: Immediately flush contaminated areas with water. Remove contaminated clothing, jewelry, and shoes immediately. Wash contaminated areas with soap and water. Thoroughly clean and dry contaminated clothing and shoes before reuse. GET MEDICAL ATTENTION IMMEDIATELY.

HYDROCHLORIC ACID (HCl) (ALL GRADES)

NA_EN

MSDS No.: M34514

Rev. Date: 09-Aug-2012

Rev. Num. 06

EYE CONTACT: Immediately flush eyes with a directed stream of water for at least 15 minutes, forcibly holding eyelids apart to ensure complete irrigation of all eye and lid tissues. Washing eyes within several seconds is essential to achieve maximum effectiveness. GET MEDICAL ATTENTION IMMEDIATELY.

INGESTION: Not a likely route of exposure.

5. FIRE-FIGHTING MEASURES

Fire Hazard: Negligible fire hazard.

Extinguishing Media: Use media appropriate for surrounding fire.

Fire Fighting: Keep unnecessary people away, isolate hazard area and deny entry. Wear NIOSH approved positive-pressure self-contained breathing apparatus operated in pressure demand mode. Move container from fire area if it can be done without risk. Cool non-leaking containers with water. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas.

Sensitivity to Mechanical Impact: Not sensitive.

Sensitivity to Static Discharge: Not sensitive.

Flash point: Not flammable

Hazardous Combustion Products: Hydrogen chloride, Chlorine, Hydrogen gas

6. ACCIDENTAL RELEASE MEASURES

Occupational Release: Remove sources of ignition. Wear appropriate personal protective equipment recommended in Section 8 of the SDS. Stop leak if possible without personal risk. Consider evacuation of personnel located downwind if material is leaking. Shut off ventilation system if needed. Completely contain spilled material with dikes, sandbags, etc. Neutralize with soda ash or dilute caustic soda. Collect with appropriate absorbent and place into suitable container. Liquid material may be removed with a properly rated vacuum truck. Keep out of water supplies and sewers. This material is acidic and may lower the pH of the surface waters with low buffering capacity. Releases should be reported, if required, to appropriate agencies.

7. HANDLING AND STORAGE

Storage Conditions: Store and handle in accordance with all current regulations and standards. Store in rubber-lined steel, acid-resistant plastic or glass containers. Keep container tightly closed. Store in a cool, dry area. Store in a well-ventilated area. Keep away from heat, sparks and open flames. Keep separated from incompatible substances (see Section 10 of SDS). Do not store in aluminum container or use aluminum fittings or transfer lines. Protect from physical damage. Dike and vent storage tanks.

HYDROCHLORIC ACID (HCl) (ALL GRADES)

M34514 NA_EN

MSDS No.: M34514

Rev. Date: 09-Aug-2012

Rev. Num. 06

Handling Procedures: Avoid breathing vapor or mist. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling. When mixing, slowly add to water to minimize heat generation and spattering.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Regulatory Exposure Limit(s): As listed below

Component	OSHA Final PEL TWA	OSHA Final PEL STEL	OSHA Final PEL Ceiling
Hydrogen chloride 7647-01-0	-----	-----	5 ppm 7 mg/m ³

OEL: Occupational Exposure Limit; **OSHA:** United States Occupational Safety and Health Administration; **PEL:** Permissible Exposure Limit; **TWA:** Time Weighted Average; **STEL:** Short Term Exposure Limit

Non-Regulatory Exposure Limit(s): As listed below

Component	CAS Number	ACGIH TWA	ACGIH STEL	ACGIH Ceiling	OSHA TWA (Vacated)	OSHA STEL (Vacated)	OSHA Ceiling (Vacated)
Hydrogen chloride	7647-01-0	-----	-----	2 ppm	-----	-----	5 ppm 7 mg/m ³

The American Conference of Governmental Industrial Hygienists (ACGIH) is a voluntary organization of professional industrial hygiene personnel in government or educational institutions in the United States. The ACGIH develops and publishes recommended occupational exposure limits each year called Threshold Limit Values (TLVs) for hundreds of chemicals, physical agents, and biological exposure indices.

ENGINEERING CONTROLS: Use closed systems when possible. Provide local exhaust ventilation where vapor or mist may be generated. Ensure compliance with applicable exposure limits.

PERSONAL PROTECTIVE EQUIPMENT:

Eye Protection: Wear chemical safety goggles with a face-shield to protect against eye and skin contact when appropriate. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Skin and Body Protection: Wear chemical resistant clothing and rubber boots when potential for contact with the material exists. Always place pants legs over boots.

Hand Protection: Wear appropriate chemical resistant gloves. Consult a glove supplier for assistance in selecting an appropriate chemical resistant glove.

Protective Material Types: Nitrile, Neoprene, Butyl rubber, Polyvinyl chloride (PVC), Responder®, Trellchem®, HPS, Tychem®

Component	Immediately Dangerous to Life/ Health (IDLH)
Hydrogen chloride	50 ppm IDLH

Respiratory Protection: A NIOSH approved full-face respirator equipped with acid gas cartridges (appropriate for hydrogen chloride) may be permissible when symptoms have been observed that are indicative of overexposure. When the level may be above the IDLH, use an SCBA or pressure-demand supplied air with an auxiliary self-contained escape pack. Pressure-demand SCBA (self-contained breathing apparatus) must be used when there is a potential for uncontrolled release or unknown concentrations. A respiratory protection program that meets 29 CFR 1910.134 must be followed whenever workplace conditions warrant use of a respirator.

HYDROCHLORIC ACID (HCl) (ALL GRADES)

M34514 NA_EN

MSDS No.: M34514

Rev. Date: 09-Aug-2012

Rev. Num. 06

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Appearance:	Clear
Color:	Colorless
Odor:	Irritating, Pungent, Sharp
Odor Threshold:	0.3 ppm (causes olfactory fatigue)
Molecular Weight:	36.46
Molecular Formula:	HCl
Boiling Point/Range:	140 - 221°F (60 - 105 °C)
Freezing Point/Range:	-29 to 5 °F (-34 to -15 °C)
Vapor Pressure:	14.6 - 80 mmHg @ 20 °C
Vapor Density (air=1):	1.3 @ 20 °C
Specific Gravity (water=1):	1.05 - 1.18
Density:	8.75 - 9.83 lbs/gal
Water Solubility:	100%
pH:	2 @ (0.2% solution)
Volatility:	9 - 36% by volume
Evaporation Rate (ether=1):	< 1.00 (butyl acetate = 1)
Flash point:	Not flammable

10. STABILITY AND REACTIVITY

Reactivity/ Stability: Stable at normal temperatures and pressures.

Conditions to Avoid: Avoid heat, flames, sparks and other sources of ignition. Avoid contact with water. Will react with some metals forming flammable hydrogen gas. Hydrogen chloride may react with cyanide, forming lethal concentrations of hydrocyanic acid. Avoid contact with incompatible materials.

Incompatibilities/ Materials to Avoid: Metals, Alkalis, Oxidizing agents, Mercuric sulfate, Perchloric acid, Carbides of calcium, cesium, rubidium, Acetylides of cesium and rubidium, Phosphides of calcium and uranium, Lithium silicide

Hazardous Decomposition Products: chlorine, hydrogen chloride, hydrogen gas

Hazardous Polymerization: Will not occur

11. TOXICOLOGICAL INFORMATION

IRRITATION DATA: As listed below

Standard Draize (Eye):	rabbit-eye mild
Standard Draize (Skin):	human-skin mild

HYDROCHLORIC ACID (HCl) (ALL GRADES)

M34514 NA_EN

MSDS No.: M34514

Rev. Date: 09-Aug-2012

Rev. Num. 06

TOXICITY DATA:

Component	LD50 Oral:	LC50 Inhalation:	LD50 Dermal:
Hydrogen chloride	700 mg/kg (Rat)	3124 ppm (1 hr-Rat)	5010 mg/kg (Rabbit)
Water	900 mg/kg (Rabbit)	1108 ppm (1hr-Rat)	

TOXICITY:

Inhalation will cause severe irritation and possible burns with coughing and choking. If inhaled deeply, edema and hemorrhage of the lungs may occur. Prolonged exposure may cause discoloration and/or erosion of teeth. Contact with eyes causes immediate severe irritation with possible burns, permanent visual impairment, or total loss of sight. Skin contact with this material may cause severe irritation and corrosion of tissue. Ingestion may cause immediate burns of the mouth, esophagus, and stomach. Ingestion may cause intense pain, nausea, vomiting, bleeding, circulating collapse, shock, and death.

CARCINOGENICITY: This product is not classified as a carcinogen by NTP, IARC or OSHA.

12 ECOLOGICAL INFORMATION

ECOTOXICITY DATA:

- **Aquatic Toxicity:**
LC50 Gambusia affinis: 282 mg/L 96 hr.
- **Fish Toxicity:**
LC50 Goldfish: 178 mg/L (1 to 2 hour survival time)
- **Freshwater Fish Toxicity:**
LC50 Bluegill: 3.6 mg/L 48 hr
- **Invertebrate Toxicity:**
LC50 Shrimp: 100 - 330 mg/L

FATE AND TRANSPORT:

BIODEGRADATION: This material is inorganic and not subject to biodegradation.

PERSISTENCE: This material is believed not to persist in the environment. This material is believed to exist in the dissociated state in the environment. If released to soil, hydrogen chloride will sink into the soil. The acid will dissolve some soil material (in particular, anything with a carbonate base) and will be somewhat neutralized. The remaining portion is thought to transport downward to the water table. If released to water, it dissociates almost completely and will be neutralized by natural alkalinity and carbon dioxide.

BIOCONCENTRATION: This material is not expected to bioconcentrate in organisms.

ADDITIONAL ECOLOGICAL INFORMATION: This material has exhibited toxicity to terrestrial organisms. May decrease pH of waterways and adversely affect aquatic life.

HYDROCHLORIC ACID (HCl) (ALL GRADES)

M34514 NA_EN

MSDS No.: M34514

Rev. Date: 09-Aug-2012

Rev. Num. 06

13. DISPOSAL CONSIDERATIONS

Reuse or reprocess, if possible. All disposals of this material must be done in accordance with local, state and federal regulations. Dispose in accordance with all applicable regulations. May be subject to disposal regulations: U.S. EPA 40 CFR 261.

14. TRANSPORT INFORMATION

U.S. DOT 49 CFR 172.101:

UN NUMBER: UN1789
PROPER SHIPPING NAME: Hydrochloric acid solution
HAZARD CLASS/DIVISION: 8
PACKING GROUP: II
LABELING: 8
REQUIREMENTS:
RQ (lbs): RQ 5,000 Lbs. (Hydrochloric acid)

CANADIAN TRANSPORTATION OF DANGEROUS GOODS:

UN NUMBER: UN1789
SHIPPING NAME: Hydrochloric acid solution
CLASS OR DIVISION: 8
PACKING/RISK GROUP: II

15. REGULATORY INFORMATION

U.S. REGULATIONS

OSHA REGULATORY STATUS:

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

CERCLA SECTIONS 102a/103 HAZARDOUS SUBSTANCES (40 CFR 302.4): If a release is reportable under CERCLA section 103, notify the state emergency response commission and local emergency planning committee. In addition, notify the National Response Center at (800) 424-8802 or (202) 426-2675.

Component	CERCLA Reportable Quantities:
Hydrogen chloride	5000 lb (final RQ)

EPCRA EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355.30):

If a release is reportable under EPCRA, notify the state emergency response commission and local emergency planning committee. If the TPQ is met, facilities are subject to reporting requirements under EPCRA Sections 311 and 312.

HYDROCHLORIC ACID (HCl) (ALL GRADES)

M34514 NA_EN

MSDS No.: M34514

Rev. Date: 09-Aug-2012

Rev. Num. 06

Component	EPCRA RQs	Threshold Planning Quantity (TPQs)
Hydrogen chloride	5000 lb (EPCRA RQ)	500 lb (TPQ) gas only

EPCRA SECTIONS 311/312 HAZARD CATEGORIES (40 CFR 370.10):

Acute Health Hazard, Reactive Hazard

EPCRA SECTION 313 (40 CFR 372.65):

The following chemicals are listed in 40 CFR 372.65 and may be subject to Community Right-to Know Reporting requirements.

Component	Status
Hydrogen chloride	Listed – Aerosol form only

OSHA PROCESS SAFETY (PSM) (29 CFR 1910.119): Not regulated

NATIONAL INVENTORY STATUS

U.S. INVENTORY STATUS: Toxic Substance Control Act (TSCA): All components are listed or exempt

TSCA 12(b): This product is not subject to export notification

Canadian Chemical Inventory: All components of this product are listed on either the DSL or the NDSL.

STATE REGULATIONS

California Proposition 65:

This product is not listed, but it may contain impurities/trace elements known to the State of California to cause cancer or reproductive toxicity as listed under Proposition 65 State Drinking Water and Toxic Enforcement Act.

Hydrogen chloride	
California Proposition 65 Cancer WARNING:	Not Listed
California Proposition 65 CRT List - Male reproductive toxin:	Not Listed
California Proposition 65 CRT List - Female reproductive toxin:	Not Listed
Massachusetts Right to Know Hazardous Substance List	Listed
New Jersey Right to Know Hazardous Substance List	sn 1012; sn 2909 (gas only)
New Jersey Special Health Hazards Substance List	corrosive
New Jersey - Environmental Hazardous Substance List	Listed
Pennsylvania Right to Know Hazardous Substance List	Listed
Pennsylvania Right to Know Special Hazardous Substances	Not Listed
Pennsylvania Right to Know Environmental Hazard List	Listed
Rhode Island Right to Know Hazardous Substance List	Listed

CANADIAN REGULATIONS

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

Canada - CEPA Schedule 1, Toxic Substance List	Not Listed
WHMIS - Classifications of Substances:	E - Corrosive material

HYDROCHLORIC ACID (HCl) (ALL GRADES)

M34514 NA_EN

MSDS No.: M34514

Rev. Date: 09-Aug-2012

Rev. Num. 06

16. OTHER INFORMATION

Prepared by: OxyChem Corporate HESS - Product Stewardship

Disclaimer:

This information is intended solely for the use of individuals trained in the NFPA and/or HMIS systems.

HMIS: (SCALE 0-4) (Rated using National Paint & Coatings Association HMIS: Rating Instructions, 2nd Edition)

Health: 3 Flammability: 0 Reactivity: 1

NFPA 704 - Hazard Identification Ratings (SCALE 0-4)

Health: 3 Flammability: 0 Reactivity: 1

Reason for Revision:

- Updated 24 Hour Emergency Telephone Number: SEE SECTION 1
- PPE recommendations have been modified: SEE SECTION 8
- Updated Transportation Information: SEE SECTION 14
- Revised California Proposition 65 Statement: SEE SECTION 15
- Revised Preparer Information: SEE SECTION 16
- Added "End of Safety Data Sheet" phrase

IMPORTANT:

The information presented herein, while not guaranteed, was prepared by technical personnel and is true and accurate to the best of our knowledge. NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTY OR GUARANTY OF ANY OTHER KIND, EXPRESS OR IMPLIED, IS MADE REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY OR OTHERWISE. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, storage, disposal and other factors that may involve other or additional legal, environmental, safety or performance considerations, and OxyChem assumes no liability whatsoever for the use of or reliance upon this information. While our technical personnel will be happy to respond to questions, safe handling and use of the product remains the responsibility of the customer. No suggestions for use are intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patents or to violate any Federal, State, local or foreign laws.

OSHA Standard 29 CFR 1910.1200 requires that information be provided to employees regarding the hazards of chemicals by means of a hazard communication program including labeling, safety data sheets, training and access to written records. We request that you, and it is your legal duty to, make all information in this Safety Data Sheet available to your employees.

End of Safety Data Sheet

Section 1. Identification

Product identifier : CRONOX™ AK-50 CORROSION INHIBITOR
™ a trademark of Baker Hughes Incorporated.

Product code : CROAK50

Relevant identified uses of the substance or mixture and uses advised against

Identified uses Acid Corrosion Inhibitor.

Uses advised against Not applicable.

Print date : 2/24/2017

Validation date : 2/24/2017

Version : 1

Supplier's details : Baker Hughes Canada Company
5050 47th Street S.E.
Calgary, Alberta, T2B 3S1
Canada
For Product Information: 281-276-5400
(8:00 a.m. - 5:00 p.m. CST, Monday - Friday)

Emergency telephone number (with hours of operation) : CHEMTREC: 800-424-9300 (U.S. 24 hour)
Baker Petrolite: 800-231-3606 (North America 24 hour)
CANUTEC: 613-996-6666 (Canada 24 hours)
CHEMTREC Int'l 01-703-527-3887

Section 2. Hazard identification

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 3
ACUTE TOXICITY (oral) - Category 4
ACUTE TOXICITY (dermal) - Category 3
ACUTE TOXICITY (inhalation) - Category 3
SKIN IRRITATION - Category 2
EYE IRRITATION - Category 2A
SKIN SENSITIZATION - Category 1
GERM CELL MUTAGENICITY - Category 2
CARCINOGENICITY - Category 2
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (kidneys and liver) - Category 2
AQUATIC HAZARD (ACUTE) - Category 2
AQUATIC HAZARD (LONG-TERM) - Category 2
Health Hazards Not Otherwise Classified - Category 1

GHS label elements

Hazard pictograms :



Section 2. Hazard identification

Signal word : Danger

Hazard statements : Flammable liquid and vapor.
 Toxic in contact with skin or if inhaled.
 Harmful if swallowed.
 Causes serious eye irritation.
 Causes skin irritation.
 Prolonged or repeated contact may dry skin and cause irritation.
 May cause an allergic skin reaction.
 Suspected of causing genetic defects.
 Suspected of causing cancer.
 May cause respiratory irritation.
 May cause drowsiness or dizziness.
 May cause damage to organs through prolonged or repeated exposure. (kidneys, liver)
 Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

Response : Collect spillage. Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician. IF SWALLOWED: Call a POISON CENTER or physician if you feel unwell. Rinse mouth. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF ON SKIN: Take off immediately all contaminated clothing and wash it before reuse. Wash with plenty of soap and water. Call a POISON CENTER or physician if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Storage : Store locked up.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements : Avoid contact with skin and clothing. Wash thoroughly after handling.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	% (w/w)	CAS number
Oxyalkylated alkylphenol	10 - 20	68891-11-2
Heavy aromatic naphtha	10 - 20	64742-94-5
Isopropanol	10 - 20	67-63-0
Fatty acids	5 - 10	61790-12-3
Complex alkylaryl polyo-ester	5 - 10	68188-40-9
Tar bases, quinoline derivs., benzyl chloride-quaternized	5 - 10	72480-70-7
Formaldehyde	5 - 10	50-00-0
Acetylenic alcohol	1 - 5	5877-42-9
Propargyl alcohol	1 - 5	107-19-7
Naphthalene	1 - 5	91-20-3

Section 4. First-aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Continue to rinse for at least 15 minutes. Check for and remove any contact lenses. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 15 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Toxic if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : Toxic in contact with skin. Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion** : Harmful if swallowed. Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

- Eye contact** : pain or irritation, watering, redness
- Inhalation** : respiratory tract irritation, coughing, nausea or vomiting, headache, drowsiness/fatigue, dizziness/vertigo, unconsciousness
- Skin contact** : irritation, redness, dryness, cracking
- Ingestion** : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

Specific hazards arising from the chemical : Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products : carbon dioxide, carbon monoxide, nitrogen oxides, sulfur oxides, halogenated compounds

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Section 6. Accidental release measures

- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Isopropanol	ACGIH TLV (United States, 4/2014). STEL: 400 ppm, 0 times per shift, 15 minutes. TWA: 200 ppm, 0 times per shift, 8 hours.
Formaldehyde	ACGIH TLV (United States, 3/2015). Skin sensitizer. Inhalation sensitizer. C: 0.3 ppm C: 0.37 mg/m ³
Propargyl alcohol	ACGIH TLV (United States, 3/2015). Absorbed through skin. TWA: 2.3 mg/m ³ , 0 times per shift, 8 hours.

Section 8. Exposure controls/personal protection

Naphthalene

TWA: 1 ppm, 0 times per shift, 8 hours.
ACGIH TLV (United States, 3/2015). Absorbed through skin.
 TWA: 52 mg/m³, 0 times per shift, 8 hours.
 TWA: 10 ppm, 0 times per shift, 8 hours.

Consult local authorities for acceptable exposure limits.

If OSHA permissible exposure levels are shown above they are the OSHA 1989 levels or are from subsequent OSHA regulatory actions. Although the 1989 levels have been vacated the 11th Circuit Court of Appeals, Baker Hughes recommends that these lower exposure levels be observed as reasonable worker protection.

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Wear chemical safety goggles. When transferring material wear face-shield in addition to chemical safety goggles.

Hand protection : Chemical-resistant gloves.

Skin protection : Wear long sleeves to prevent repeated or prolonged skin contact.

Respiratory protection : If a risk assessment indicates it is necessary, use a properly fitted, air purifying or supplied air respirator complying with an approved standard. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid.

Color : Amber.

Odor : Pungent.

Odor threshold : Not available.

pH : Not available.

Melting/freezing point : Not available.

Boiling point : Not available.

Initial Boiling Point : Not available.

Flash point : Closed cup: 37.8°C (100°F) [SFCC]

Burning time : Not applicable.

Burning rate : Not applicable.

Evaporation rate : Not available.

Flammability (solid, gas) : Flammable in the presence of the following materials or conditions: open flames, sparks and static discharge and heat.

Lower and upper explosive (flammable) limits : Not available.

Vapor pressure : 5 kPa (37.2 mm Hg) @ 37.8°C

Section 9. Physical and chemical properties

Vapor density	: >1 [Air = 1]
Relative density	: 0.9664 (15.6°C)
Density	: 8.05 (lbs/gal)
Solubility in water	: Insoluble
Partition coefficient: n-octanol/water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Dynamic (15.6°C): 38 cP
VOC	: Not available.
Pour Point	: -23.3°C (-9.9°F)

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials, acids and alkalis. Isopropanol is incompatible with acrylaldehyde, aluminum powder, and potassium tert-butoxide.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Heavy aromatic naphtha	LC50 Inhalation Vapor	Rat	>11.4 mg/l	6 hours
	LD50 Oral	Rat	3200 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
Isopropanol	LC50 Inhalation Vapor	Rat	>10000 ppm	6 hours
	LD50 Dermal	Rabbit	6.29 g/kg	-
	LD50 Oral	Rat	5000 mg/kg	-
Fatty acids	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>10000 mg/kg	-
	LD50 Oral	Rat	800 mg/kg	-
Formaldehyde	LD50 Dermal	Rabbit	270 mg/kg	-
	LD50 Oral	Rat	640 mg/kg	-
	LD50 Oral	Rat	4100 mg/kg	-
Acetylenic alcohol	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	4100 mg/kg	-
Propargyl alcohol	LC50 Inhalation Vapor	Rat	2000 mg/m ³	2 hours
	LD50 Oral	Rat	55 mg/kg	-
	LD50 Oral	Rat	55 mg/kg	-

Section 11. Toxicological information

Naphthalene CRONOX™ AK-50 CORROSION INHIBITOR	LD50 Dermal	Rabbit	>20 g/kg	-
	LD50 Dermal	Rabbit	630 mg/kg	-
	LD50 Oral	Rat	1400 mg/kg	-

Irritation/Corrosion

No applicable toxicity data

Sensitization

No applicable toxicity data

Mutagenicity

No applicable toxicity data

Carcinogenicity

Product/ingredient name	OSHA	IARC	NTP
Isopropanol	-	3	-
Formaldehyde	+	1	Known to be a human carcinogen.
Naphthalene	-	2B	Reasonably anticipated to be a human carcinogen.

Reproductive toxicity

No applicable toxicity data

Teratogenicity

No applicable toxicity data

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Heavy aromatic naphtha	Category 3	Not applicable.	Narcotic effects
Isopropanol	Category 3	Not applicable.	Narcotic effects
Formaldehyde	Category 3	Not applicable.	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Propargyl alcohol	Category 2	Inhalation	kidneys and liver

Aspiration hazard

Name	Result
Heavy aromatic naphtha	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Routes of entry anticipated: Dermal, Inhalation.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Section 11. Toxicological information

General	: May cause damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: Suspected of causing genetic defects.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Inhalation (vapors)	8.145 mg/l

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Isopropanol	Acute LC50 1400000 µg/l Marine water	Crustaceans - Crangon crangon	48 hours
	Acute LC50 1400000 µg/l	Fish - Gambusia affinis	96 hours
Formaldehyde	Acute EC50 0.788 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 12.98 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia	48 hours
	Acute EC50 14000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 1.41 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 100 µg/l Marine water	Algae - Phyllospora comosa	96 hours
Propargyl alcohol	EC50 98.1 mg/l	Algae	72 hours
	Acute EC50 3.36 mg/l	Daphnia	48 hours
	Acute LC50 4.64 mg/l	Fish	96 hours
Naphthalene	Acute EC50 1.6 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 2350 µg/l Marine water	Crustaceans - Palaemonetes pugio	48 hours
	Acute LC50 213 µg/l Fresh water	Fish - Melanotaenia fluviatilis - Larvae	96 hours
	Chronic NOEC 0.67 ppm Fresh water	Fish - Oncorhynchus kisutch	40 days

Persistence and degradability













Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Propargyl alcohol	-	-	Readily

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	IMDG	IATA
UN number	UN1992	UN1992	UN1992	UN1992
UN proper shipping name	FLAMMABLE LIQUID, TOXIC, N.O.S. (Contains: Isopropanol, Propargyl alcohol)	FLAMMABLE LIQUID, TOXIC, N.O.S. (Contains: Isopropanol, Propargyl alcohol)	FLAMMABLE LIQUID, TOXIC, N.O.S. (Contains: Isopropanol, Propargyl alcohol)	FLAMMABLE LIQUID, TOXIC, N.O.S. (Contains: Isopropanol, Propargyl alcohol)
Transport hazard class(es)	3 (6.1)   	3 (6.1)   	3 (6.1)   	3 (6.1)   
Packing group	III	III	III	III
Environmental hazards	Yes.	Yes.	Yes.	No.
Additional information	-	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3), 2.26-2.36 (Class 6)	Emergency schedules (EmS) F-E S-E	-

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to Annex II of MARPOL and the IBC Code : Not available.

DOT Reportable Quantity Formaldehyde, 167 gal of this product.
Propargyl alcohol, 2535 gal of this product.
Naphthalene, 837 gal of this product.

Section 14. Transport information

Marine pollutant Heavy aromatic naphtha
Acetylenic alcohol

North-America NAERG : 131

Section 15. Regulatory information

Canadian lists

Canadian NPRI : The following components are listed: Formaldehyde; Heavy aromatic solvent naphtha; Naphthalene; Isopropyl alcohol; Propargyl alcohol

CEPA Toxic substances : The following components are listed: Formaldehyde; Naphthalene

Canada (CEPA DSL): : At least one component is not listed in DSL but all such components are listed in NDSL.

Inventory list

United States : All components are listed or exempted.

Additional information

This product contains a chemical (CAS No. 72480-70-7 - tar bases, quinoline derivatives, benzyl chloride-quaternized) that has not been placed on the DSL due to a suspicion of being toxic. Environment Canada has imposed a condition which allows the importation of this substance for the purpose of use as an acid corrosion inhibitor employed in the stimulation of oil and gas wells. This substance should not be discharged into water and disposal is limited to deep-well injection. All users must be notified of these conditions in writing.

Section 16. Other information

National Fire Protection Association (U.S.A.)



History

Date of printing : 2/24/2017

Notice to reader

NOTE: The information on this SDS is based on data which is considered to be accurate. Baker Hughes, however, makes no guarantees or warranty, either expressed or implied of the accuracy or completeness of this information.

The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of this product.

This SDS was prepared and is to be used for this product. If the product is used as a component in another product, this SDS information may not be applicable.

NC 1

NE-6 Material Safety Data Sheet

Section 1. Chemical Product and Company Identification			
Product Name	ARBREAK 8792 DEMULSIFIER	Code	ARB8792
Supplier	Aquaness Chemical A Division Of Baker Petrolite Corporation A Baker Hughes company 12645 W. Airport Blvd. (77478) P.O. Box 5050 Sugar Land, TX 77487-5050 For Product Information/MSDSs Call: 800-231-3606 (8:00 a.m. - 5:00 p.m. est, Monday - Friday)	Version	1.0
Material Uses	Demulsifier.	Effective Date	12/14/2004
24 Hour Emergency Numbers	CHEMTREC 800-424-9300 (U.S. 24 hour) Baker Petrolite 800-231-3606 (North America 24 hour) CANUTEC 613-006-6866 (Canada 24 hours)	Print Date	12/14/2004
<p>National Fire Protection Association (U.S.A.)</p> <p>Health 2 Flammability 2 Reactivity 0 Specific Hazard 0</p>			

Section 2. Composition and Information on Ingredients			
Name	CAS #	% by Weight	Exposure Limits
Light aromatic naphtha	64742-95-6	30-60	Not available.
1,2,4-Trimethylbenzene	95-63-6	10-30	Not available.
1,2,3-Trimethylbenzene	526-73-8	1-5	Not available.
1,3,5-Trimethylbenzene	108-67-8	6-10	Not available.
Xylene	1330-20-7	1-5	ACGIH (United States). TWA: 434 mg/m ³ 8 hour(s). STEL: 651 mg/m ³ 15 minute(s). TWA: 100 ppm 8 hour(s). STEL: 160 ppm 15 minute(s). OSHA (United States). TWA: 100 ppm 8 hour(s). STEL: 150 ppm 15 minute(s). TWA: 435 mg/m ³ 8 hour(s). STEL: 655 mg/m ³ 15 minute(s).
2-Ethylhexanol	104-76-7	5-10	Manufacturer TWA: 20 ppm
While trimethylbenzene isomers do not have exposure limits, trimethylbenzene (mixed isomers)(CAS No. 25551-13-7) has TWA value of 25 ppm for both ACGIH and OSHA (revoked limit).			

Continued on Next Page

ARBREAK 8792 DEMULSIFIER

Page: 2/9

Section 3. Hazards Identification

Physical State and Appearance	State: Liquid., Color: Dark Brown., Odor: Acidic. Aromatic hydrocarbon.
CERCLA Reportable Quantity	Xylene 793 gal.
Hazard Summary	WARNING. May cause chronic effects. Combustible liquid. At elevated temperatures, vapors can form an ignitable or explosive mixture with air. Can form explosive mixtures at temperatures at or above the flash point. Vapors can flow along surfaces to distant ignition sources and flash back. Static discharges can cause ignition or explosion when container is not bonded. May be irritating to eyes, skin and respiratory tract. May cause central nervous system (CNS) effects if inhaled.
Routes of Exposure	Skin (Contact), Eyes, Inhalation.
Potential Acute Health Effects	Eyes May be severely irritating to the eyes. Skin May be irritating to skin. Inhalation May cause central nervous system (CNS) effects if inhaled. May be irritating to lungs. Ingestion Not considered a likely route of exposure, however, may be harmful or cause irritation if swallowed.
Medical Conditions aggravated by Exposure	Exposure to this product may aggravate medical conditions involving the following: blood system, kidneys, nervous system, liver, gastrointestinal tract, respiratory tract, skin/epithelium, eyes.
See Toxicological Information (section 11)	
Additional Hazard Identification Remarks	May be harmful if ingested. This product may be aspirated into the lungs during swallowing or vomiting of swallowed material. Aspiration into the lungs may produce chemical pneumonitis, pulmonary edema, and hemorrhaging. Repeated or prolonged contact may cause dermatitis (inflammation) and defatting of the skin (dryness).

Section 4. First Aid Measures

Eye Contact	Flush eyes with plenty of water for 15 minutes, occasionally lifting upper and lower eyelids. Get medical attention immediately.
Skin Contact	Remove and launder or clean contaminated clothing and shoes. Wash with soap and water for at least 15 minutes or until no evidence of material remains. Get medical attention if irritation occurs.
Inhalation	Remove to fresh air. Oxygen may be administered if breathing is difficult. If not breathing, administer artificial respiration and seek medical attention. Get medical attention if symptoms appear.
Ingestion	If swallowed, do not induce vomiting unless directed to do so by medical personnel. Never induce vomiting or give anything by mouth to a victim who is unconscious or having convulsions. Get medical attention if symptoms appear.
Notes to Physician	Not available.
Additional First Aid Remarks	If product is ingested and vomiting occurs naturally, have person lean forward to reduce the risk of aspiration into the lungs. If breathing has stopped or the heart has stopped, trained personnel should immediately administer artificial respiration or cardiopulmonary resuscitation, as required.

Continued on Next Page

ARBREAK 8792 DEMULSIFIER

Page: 3/9

Section 5. Fire Fighting Measures	
Flammability of the Product	Combustible liquid. At elevated temperatures, vapors can form an ignitable or explosive mixture with air. Can form explosive mixtures at temperatures at or above the flash point. Vapors can flow along surfaces to distant ignition sources and flash back. Static discharges can cause ignition or explosion when container is not bonded.
OSHA Flammability Class	II
Autoignition temperature	Not available.
Flash Points	Closed cup: 48.7°C (116°F). (PMCC)
Flammable Limits	L.E.L. Not available, U.E.L. Not available.
Products of Combustion	These products are carbon oxides (CO, CO ₂) nitrogen oxides (NO, NO ₂ ...) sulfur oxides (SO ₂ , SO ₃ ...).
Fire Hazards in Presence of Various Substances	Open Flames/Sparks/Static. Heat.
Fire Fighting Media and Instructions	In case of fire, use foam, dry chemicals, or CO ₂ fire extinguishers. Evacuate area and fight fire from a safe distance. Water spray may be used to keep fire-exposed containers cool. Keep water run off out of sewers and public waterways. Note that flammable vapors may form an ignitable mixture with air. Vapors may travel considerable distances and flash back if ignited.
Protective Clothing (Fire)	Do not enter fire area without proper personal protective equipment, including NIOSH approved self-contained breathing apparatus.
Special Remarks on Fire Hazards	Not available.

Section 6. Accidental Release Measures	
Spill	Put on appropriate personal protective equipment. Keep personnel removed and upwind of spill. Shut off all ignition sources; no flares, smoking, or flames in hazard area. Approach release from upwind. Shut off leak if it can be done safely. Contain spilled material. Keep out of waterways. Dike large spills and use a non-sparking or explosion-proof means to transfer material to an appropriate container for disposal. For small spills add absorbent (soil may be used in the absence of other suitable materials) scoop up material and place in a sealed, liquid-proof container. Note that flammable vapors may form an ignitable mixture with air. Vapors may travel considerable distances from spill and flash back, if ignited. Waste must be disposed of in accordance with federal, state and local environmental control regulations.
Other Statements	If RQ (Reportable Quantity) is exceeded, report to National Spill Response Office at 1-800-424-8802.
Additional Accidental Release Measures Remarks	Not available.

Continued on Next Page

ARBREAK 8792 DEMULSIFIER

Page: 4/9

Section 7. Handling and Storage

Handling and Storage Put on appropriate personal protective equipment. Avoid contact with eyes, skin, and clothing. Avoid breathing vapors or spray mists. Use only with adequate ventilation. Store in a dry, cool and well ventilated area. Keep away from heat, sparks and flame. Keep away from incompatibles. Keep container tightly closed and dry. To avoid fire or explosion, ground container equipment and personnel before handling product.

Additional Handling and Storage Remarks Not available.

Section 8. Exposure Controls/Personal Protection

Engineering Controls Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors or particles below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Personal Protection

Personal Protective Equipment recommendations are based on anticipated known manufacturing and use conditions. These conditions are expected to result in only incidental exposure. A thorough review of the job tasks and conditions by a safety professional is recommended to determine the level of personal protective equipment appropriate for these job tasks and conditions.

Eyes Chemical safety goggles.

Body Wear long sleeves to prevent repeated or prolonged skin contact.

Respiratory Respirator use is not expected to be necessary under normal conditions of use. In poorly ventilated areas, emergency situations or if exposure levels are exceeded, use NIOSH approved full face respirator.

Hands Chemical resistant gloves. Nitrile or Neoprene gloves, 4H gloves.

Feet Chemical resistant boots or overshoes.

Other Information Not available.

Additional Exposure Control Remarks Not available.

Section 9. Typical Physical and Chemical Properties

Physical State and Appearance	Liquid,	Odor	Acidic, Aromatic hydrocarbon.
pH	8.5 - 9.5 (5% of product in 75% isopropanol / 25% water solution)	Color	Dark Brown.
Specific gravity	0.962 - 0.964 @ 16°C (60°F)		
Density	7.93 - 8.03 lbs/gal @ 16°C (60°F)		
Vapor Density	>1 (Air = 1)		
Vapor Pressure	7.6 - mmHg @ 21°C (70°F) Calculated Value for all Components.		
Evaporation Rate	Not Available or Not Applicable for Solids.		
VOC	Not available.		
Viscosity	11 - 12 cps @ 38°C (100°F) Kinematic		
Pour Point	-40°C (-40°F)		
Solubility (Water)	Dispersible		
Boiling Point	Not available.		

Continued on Next Page

ARBREAK 8792 DEMULSIFIER		Page: 519
Physical Chemical	Not available.	
Comments		

Section 10. Stability and Reactivity	
Stability and Reactivity	The product is stable.
Conditions of Instability	Not available.
Incompatibility with Various Substances	Oxidizing material.
Hazardous Decomposition Products	Not applicable.
Hazardous Polymerization	Hazardous polymerization is not expected to occur.
Special Stability & Reactivity Remarks	Not available.

Section 11. Toxicological Information	
<u>Component Toxicological Information</u>	
Acute Animal Toxicity	
Light aromatic naphtha	ORAL (LD50): Acute: 2900 mg/kg [Rat]. 8400 mg/kg [Rat].
1,2,4-Trimethylbenzene	ORAL (LD50): Acute: 5000 mg/kg [Rat]. VAPOR (LC50): Acute: 18000 mg/m ³ 4 hour(s) [Rat].
1,2,3-Trimethylbenzene	Not available.
1,3,5-Trimethylbenzene	VAPOR (LC50): Acute: 24000 mg/m ³ 4 hour(s) [Rat].
Xylene	ORAL (LD50): Acute: 4300 mg/kg [Rat]. 3523 mg/kg [Male rat]. DERMAL (LD50): Acute: >1700 mg/kg [Rabbit]. VAPOR (LC50): Acute: 5000 ppm 4 hour(s) [Rat].
2-Ethylhexanol	ORAL (LD50): Acute: 3730 mg/kg [Rat]. 2500 mg/kg [Mouse]. DERMAL (LD50): Acute: 1970 mg/kg [Rabbit].
Chronic Toxicity Data	
1) Light aromatic naphtha	
	Ingestion has produced Central Nervous System effects in laboratory animals. (EPA/OTS 87-8214199 and 88-920000348)
2) 1,2,4-Trimethylbenzene	
	1,2,4-Trimethylbenzene, also known as pseudocumene, is a component of this product. Chronic pseudocumene exposure may provoke bronchospasm with cough and wheezing (Punkett, 1976; ACGIH, 1991; Ballig et al, 1966). Respiratory distress was noted in experimental animals following sub acute inhalation exposure (Gage, 1970). Nervousness and anxiety were noted with chronic occupational exposure (Ballig et al, 1966; ACGIH, 1991).
	At the time of this review, no studies were found on the potential adverse reproductive effects of pseudocumene in humans, but trimethylbenzenes (including pseudocumene) can cross the placental barrier (Clayton & Clayton, 1994; Doroly et al, 1976). In an experimental animal study, offspring born to pregnant rats exposed to pseudocumene were healthy at birth and grew normally (Cameron et al, 1938).
Continued on Next Page	

ARBREAK 8792 DEMULSIFIER

Page: 6/9

Blood effects such as anemia and delayed clotting time have been noticed in workers chronically exposed to a solvent containing trimethylbenzene. The blood effects, however, may have been due to a contaminant in the solvent such as benzene (a known blood toxin).

3) 1,2,3-Trimethylbenzene

Not available.

4) 1,3,5-Trimethylbenzene

1,3,5-Trimethylbenzene (Mesitylene) is a component of this product. Chronic asthmatic-like bronchitis may be a delayed chronic hazard (EPA, 1985; Laham, 1987; HSDB, 1997). Nervousness, tension, and anxiety have been noted in chronically exposed workers with exposure to a mixture of solvents including mesitylene (HSDB, 1997). Elevated alkaline phosphates and SGOT (liver enzymes) levels have been noted in chronic animal inhalation studies (Clayton & Clayton, 1994). These effects have not been reported in exposed humans. (Reprotext)

Thrombocytopenia (a lack of platelets in the blood) with bleeding from the gums and nose and mild anemia may occur with chronic exposure to mesitylene as a component of the commercial solvent mixture, "Fleet-X-DY-99" (Flunkett, 1976; Finkel, 1983; HSDB, 1997). Coagulation (clotting of the blood) times were delayed by about 40% in a group of workers chronically exposed to a mixture of solvents containing about 30% mesitylene (Laham, 1987). These hematological disorders may have been due to a contaminant, such as benzene (Hathaway et al, 1996). Thrombocytosis (an increase of platelets in the blood) and thrombocytopenia have been noted in rabbits (Clayton & Clayton, 1994). (Reprotext)

1,3,5-Trimethylbenzene has been positive in a mutagenicity assay (Lewis, 1992). (Reprotext)

5) Xylene

Xylene (mixed isomers) is a component of this product. Effects of chronic exposure to xylene are similar to those of acute exposure, but may be more severe. Chronic inhalation reportedly was associated with headache, tremors, apprehension, memory loss, weakness, dizziness, loss of appetite, nausea, ringing in the ears, irritability, thirst, anemia, mucosal bleeding, enlarged liver, and hyperplasia, but not destruction of the bone marrow (Clayton & Clayton, 1994; ILO, 1983). Some earlier reports of effects of chronic exposure to xylene have been questioned, as exposures were not limited to xylene alone.

Effects on the blood have been reported from chronic exposure to as little as 50 mg/m³ (Pap & Varga, 1987). Repeated exposure can damage bone marrow, causing low blood cell count and can damage the liver and kidneys (NJ Department of Health, Hazardous Substance Fact Sheet). Chronic xylene exposure (usually mixed with other solvents) has produced irreversible damage to the CNS (ILO, 1983). CNS effects may be exacerbated by ethanol abuse (Savolainen, 1980). Xylene may damage hearing or enhance sensitivity to noise in chronic occupational exposures (Morata et al, 1994), probably from neurotoxic mechanism. Tolerance to xylene can occur over the work week and disappear over the weekend. (ACGIH, 1992).

Inhalation exposure has produced fetotoxicity and postnatal developmental toxicity in laboratory animals. (API, 1976; Kensington, MD, EPA/OTS Document No. 878210350 and Hass, U., et al, 1996, Neurotoxicology and Teratology 17: 341-349 and 1997, Neurotoxicology 18: 547-552)

6) 2-Ethylhexanol

2-Ethylhexanol (2EH) is a component of this product. Chronic overexposure has been suggested as a cause of the following effects in laboratory animals, and may aggravate pre-existing disorders of these organs in humans: liver abnormalities, kidney damage, lung damage, cardiac abnormality, blood abnormalities, and spleen damage. (Vendor MSDS)

In subchronic oral studies, 2EH has produced liver and kidney effects in laboratory animals. (RTECS)


2EH has produced developmental effects in oral studies in laboratory animals including teratogenicity at maternally toxic doses (Clayton & Clayton, 1994), (HSDB)

Continued on Next Page

ARBREAK 8792 DEMULSIFIER		<i>Page: 7/9</i>
Product Toxicological Information		
Acute Animal Toxicity	Not available.	
Target Organs	blood system, kidneys, nervous system, liver, gastrointestinal tract, respiratory tract, skin/epithelium, eyes.	
Other Adverse Effects	Not available.	

Section 12. Ecological Information	
Ecotoxicity	Not available.
BOD5 and COD	Not available.
Biodegradable/OECD	Not available.
Toxicity of the Products of Biodegradation	Not available.
Special Remarks	Not available.

Section 13. Disposal Considerations	
Responsibility for proper waste disposal rests with the generator of the waste. Dispose of any waste material in accordance with all applicable federal, state and local regulations. Note that these regulations may also apply to empty containers, liners and rinsate. Processing, use, dilution or contamination of this product may cause its physical and chemical properties to change.	
Additional Waste Remarks	Not available.

Section 14. Transport Information		
DOT Classification	FLAMMABLE LIQUID, N.O.S. (Contains: Light aromatic naphtha, 1,2,4-Trimethylbenzene), 3, UN1993, III	
DOT Reportable Quantity	Xylene 793 gal.	
Marine Pollutant	Not applicable.	
Additional DOT information	Not available.	
Emergency Response Guide Page Number	128	

Continued on Next Page

ARBREAK 8792 DEMULSIFIER

Page: 8/9

Section 15. Regulatory Information	
HCS Classification	Target organ effects, Combustible liquid. At elevated temperatures, vapors can form an ignitable or explosive mixture with air. Can form explosive mixtures at temperatures at or above the flash point. Vapors can flow along surfaces to distant ignition sources and flash back. Static discharges can cause ignition or explosion when container is not bonded. Irritant.
U.S. Federal Regulations	
Environmental Regulations	Extremely Hazardous Substances: Not applicable to any components in this product. SARA 313 Toxic Chemical Notification and Release Reporting: 1,2,4-Trimethylbenzene; Xylene; SARA 302/304 Emergency Planning and Notification substances: Not applicable to any components in this product. Hazardous Substances (CERCLA 302): Xylene 793 gal; SARA §11/§12 MSDS distribution - chemical inventory - hazard identification: fire; immediate health hazard; delayed health hazard; Clean Water Act (CWA) 307 Priority Pollutants: Not applicable to any components in this product. Clean Water Act (CWA) 311 Hazardous Substances: Xylene; Clean Air Act (CAA) 112(r) Accidental Release Prevention Substances: Not applicable to any components in this product.
Threshold Planning Quantity (TPQ)	Not applicable.
TSCA Inventory Status	All components are included or are exempted from listing on the US Toxic Substances Control Act inventory. This product contains the following components that are subject to the reporting requirements of TSCA Section 12(b) if exported from the United States: Xylene; Naphthalene.
State Regulations	State specific information is available upon request from Baker Petrolite.
International Regulations	
Canada	All components are compliant with or are exempted from listing on the Canadian Domestic Substance List.
WHMIS (Canada)	B-3, D-2A, D-2B
European Union	All components are included or are exempted from listing on the European Inventory of Existing Commercial Chemical Substances or the European List of Notified Chemical Substances. International inventory status information is available upon request from Baker Petrolite for the following countries: Australia, China, Korea (ICCL), Philippines (RA6969), or Japan.
Harmonized Tariff Code	Not available.
Other Regulatory Information	No further regulatory information is available.

Continued on Next Page

ARBREAK 8792 DEMULSIFIER

Page: 919

Section 16. Other Information

Other Special File 2634
Considerations

Baker Petrolite Disclaimer

NOTE: The information on this MSDS is based on data which is considered to be accurate. Baker Petrolite, however, makes no guarantees or warranty, either expressed or implied of the accuracy or completeness of this information.

The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of this product.

This MSDS was prepared and is to be used for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

Safety Data Sheet



Section 1: Identification

Product Identifier

- Product Name** • PLEXGEL BREAKER XPA
Product Code • 01025

Relevant identified uses of the substance or mixture and uses advised against

- Recommended use** • Petrochemical industry

Details of the supplier of the safety data sheet

- Manufacturer** • Chemplex | Solvay USA Inc. | Novecare Division
 506 CR 137
 P.O. Box 1071 Snyder, TX 79550
 United States
 www.chemplex.net
 SDS@chemplex.net
Telephone (General) • 325.573.7298

Emergency telephone number

- Manufacturer** • 800.424.9300 - CHEMTREC

Section 2: Hazard Identification

United States (US)

According to: OSHA 29 CFR 1910.1200 HCS

Classification of the substance or mixture

- OSHA HCS 2012** • Eye Irritation 2

Label elements

OSHA HCS 2012

WARNING



- Hazard statements** • Causes serious eye irritation

Precautionary statements

- Prevention** • Wear eye/face protection - Safety glasses with side-shield, .
 Wash thoroughly after handling.
Response • IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

- Storage/Disposal**
- Store in a well-ventilated place. Keep cool.
 - Store in a well-ventilated place. Keep container tightly closed.
 - Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.
 - Wash thoroughly after handling.

Other hazards

OSHA HCS 2012

- No data available

Canada

According to: WHMIS

Classification of the substance or mixture

WHMIS

- Other Toxic Effects - D2B

Label elements

WHMIS



- Other Toxic Effects - D2B


Other hazards

WHMIS

- No other WHMIS hazards than those reported above. See all section 2 hazard statements.

Other information

- One should be specifically trained before communicating or using the following National Fire Protection Association (NFPA) and or Hazardous Materials Identification System (HMIS) categories since the definition and scales applied do not match US OSHA GHS and HAZCOM 2012 definitions and rules.



- Health Hazard: 1 - Caution: May be irritating
- Reactivity: 0 - Stable: Not reactive under normal conditions
- Flammability: 0 - Not combustible

- HMIS**
- HMIS Health - 1: Slight Hazard
 - HMIS Flammability - 0: Minimal Hazard
 - HMIS Physical Hazard - 0: Minimal Hazard

Section 3 - Composition/Information on Ingredients

Substances

- Not applicable. This material is a mixture.

Mixtures

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

Composition			
Chemical Name	Identifiers	%	Hazardous
Hydrogen peroxide	CAS:7722-84-1	5% TO 8%	Yes

- This product is considered hazardous according to the OSHA Hazard Communication Standard 29 CFR 1910.1200. Under Canadian regulations (Workplace Hazardous Materials Information System (WHMIS) - Hazardous Products Act (HPA), this material is hazardous.

Section 4: First-Aid Measures

Description of first aid measures

- Inhalation**
 - Get medical attention immediately if symptoms occur. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- Skin**
 - Get medical attention immediately if symptoms occur. Rinse skin immediately with plenty of water for 15-20 minutes. Take off contaminated clothing and wash before reuse.
- Eye**
 - Flush eyes with water for at least 15 minutes while holding eyelids open. Get medical attention immediately. If easy to do, remove contact lenses, if worn.
- Ingestion**
 - Vomiting may occur spontaneously. To prevent aspiration of swallowed product, lay victim on side. Do NOT induce vomiting. Get medical attention immediately. Give nothing to drink.

Most important symptoms and effects, both acute and delayed

- Causes serious eye irritation.

Indication of any immediate medical attention and special treatment needed

- Notes to Physician**
 - All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred. Treat symptomatically. There is no specific antidote available.

Section 5: Fire-Fighting Measures

Extinguishing media

- Suitable Extinguishing Media**
 - LARGE FIRES: Dry chemical, CO2, alcohol-resistant foam or water spray.
 - SMALL FIRES: Dry chemical, CO2, water spray or alcohol-resistant foam.

- Unsuitable Extinguishing Media**
 - DO NOT use high volume water jet.

Special hazards arising from the substance or mixture

- Unusual Fire and Explosion Hazards**
 - Hydrogen peroxide decomposes to release oxygen. Containers may explode when heated.
- Hazardous Combustion Products**
 - Hazardous combustion products may include a complex mixture of airborne solid and liquid particulates and gases (acrid smoke and irritating fumes).

Advice for firefighters

- Firefighters should wear NIOSH/MSHA approved self-contained breathing apparatus and full protective clothing. Standard procedures for chemical fires.

Collect contaminated fire extinguishing materials separately. This must be not be discharged into drains.
 Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
 Cool closed containers exposed to fire with water spray.
 Refer to Section 8 - Exposure Controls/Personal Protection.

Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

- Personal Precautions**
- Avoid contact with eyes. Wear eye/face protection. Refer to Section 8 - Exposure Controls/Personal Protection.
- Emergency Procedures**
- Keep unauthorized personnel away. Avoid all contact. Strict hygiene. Ventilate closed spaces before entering. Stop leak if you can do it without risk.

Environmental precautions

- Spills may be reportable to the National Response Center (800-424-8802) and to state and or local agencies. Do not flush to sewer or allow to enter waterways. Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems.

Methods and material for containment and cleaning up

- Containment/Clean-up Measures**
- Dike to collect large liquid spills. Contain and recover liquid when possible. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Wash remainder with plenty of water. Water will make area slippery. Repeat cleaning process until the contaminated surface is no longer slippery. Refer to Section 13 - Disposal Considerations.

- Prohibited Materials**
- Strong alkalines and oxidizing materials. Sources of ignition - heat, sparks and open flames.

Reference to other sections

- Refer to Section 8 - Exposure Controls/Personal Protection.

Section 7 - Handling and Storage

Precautions for safe handling

- Handling**
- Avoid contact with skin and eyes. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

- Storage**
- Store locked up. Keep only in the original container/package in a cool well-ventilated place. Store away from alkali(bases)and oxidizing agents. Avoid excessive heat.

- Incompatible Materials or Ignition Sources**
- Reactive with strong bases and oxidizing agents.

Refer to Section 8 - Exposure Controls/Personal Protection.

Section 8 - Exposure Controls/Personal Protection

Control parameters

- Exposure Limits/Guidelines**
- Use only with adequate ventilation. Avoid all contact. Strict hygiene.

Exposure Limits/Guidelines				
	Result	ACGIH	NIOSH	OSHA
Hydrogen peroxide (7722-84-1)	TWAs	1 ppm TWA	1 ppm TWA; 1.4 mg/m3 TWA	1 ppm TWA; 1.4 mg/m3 TWA

Exposure controls

Engineering Measures/Controls

- Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Personal Protective Equipment

Respiratory

- When respirators are required, use NIOSH/MSHA approved equipment based on actual or potential airborne concentrations and in accordance with the appropriate regulatory standards and/or industrial recommendations.

Eye/Face

- Eye and face protection requirements will vary dependent upon work environment conditions and material handling practices. Appropriate ANSI Z87 approved equipment should be selected for the particular use intended for this material. Wear eye/face protection - Safety glasses with Side-shield, .

Skin/Body

- Wear protective gloves/protective clothing/eye protection/face protection.

General Industrial Hygiene Considerations

- Avoid all contact. Strict hygiene. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Keep away from food, drink and animal feeding stuffs.

Environmental Exposure Controls

- Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways.

Additional Protection Measures

- The protective equipment must be selected in accordance with local standards and in cooperation with the supplier of the protective equipment. Selection of the appropriate personal protective equipment should be based upon an evaluation of the performance characteristics of the protective equipment relative to the tasks to be performed, conditions present, duration of use, and the potential hazards, and/or risks that may occur during use. Emergency equipment should be immediately accessible, with instructions for use. Facilities using or storing this material should be equipped with an eyewash and safety shower in close proximity to areas of storage and use.

Section 9 - Physical and Chemical Properties

Information on Physical and Chemical Properties

Material Description			
Physical Form	Liquid	Color	Red
Odor	Odorless	Odor Threshold	No data available
General Properties			
Boiling Point	214 F(101.1111 C)	Melting Point	No data available
Decomposition Temperature	No data available	pH	5.5 to 6.5
Specific Gravity/Relative Density	= 1.03 Water=1	Density	1.03 g/mL
Water Solubility	Soluble	Viscosity	No data available
Volatility			
Vapor Pressure	No data available	Vapor Density	No data available
Evaporation Rate	No data available		
Flammability			
Flash Point	No data available	UEL	No data available
LEL	No data available	Autoignition	No data available
Flammability (solid, gas)	None		
Environmental			
Octanol/Water Partition coefficient	No data available	Bioaccumulation Factor	None

Section 10: Stability and Reactivity

Reactivity

- Hydrogen peroxide decomposes to release oxygen.

Chemical stability

- This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

Possibility of hazardous reactions

- Hazardous polymerization will not occur.

Conditions to avoid

- Excess heat.

Incompatible materials

- Hydrogen peroxide decomposes to release oxygen. Keep away from combustible and flammable materials.

Hazardous decomposition products

- Hydrogen peroxide decomposes to release oxygen. Hazardous combustion products may include a complex mixture of airborne solid and liquid particulates and gases (acid smoke and irritating fumes)

Section 11 - Toxicological Information

Information on toxicological effects

GHS Properties	Classification
Acute toxicity	OSHA HCS 2012 • Acute Toxicity - Dermal - Classification criteria not met; Acute Toxicity - Inhalation - Classification criteria not met; Acute Toxicity - Oral - Classification criteria not met
Aspiration Hazard	OSHA HCS 2012 • Classification criteria not met
Carcinogenicity	OSHA HCS 2012 • Classification criteria not met
Germ Cell Mutagenicity	OSHA HCS 2012 • Classification criteria not met
Skin corrosion/Irritation	OSHA HCS 2012 • Classification criteria not met
Skin sensitization	OSHA HCS 2012 • Classification criteria not met
STOT-RE	OSHA HCS 2012 • Classification criteria not met
STOT-SE	OSHA HCS 2012 • Classification criteria not met
Toxicity for Reproduction	OSHA HCS 2012 • Classification criteria not met
Respiratory sensitization	OSHA HCS 2012 • Classification criteria not met
Serious eye damage/Irritation	OSHA HCS 2012 • Eye Irritation 2

Medical Conditions Aggravated by Exposure Potential Health Effects

- None known.

Inhalation

Acute (Immediate)

- Classification criteria not met.

Chronic (Delayed)

- No data available

Skin

- Acute (Immediate) • Classification criteria not met.
- Chronic (Delayed) • No data available

Eye

- Acute (Immediate) • Causes serious eye irritation.
- Chronic (Delayed) • No data available

Ingestion

- Acute (Immediate) • May cause burns of the gastrointestinal tract if swallowed.
- Chronic (Delayed) • No data available

Section 12 - Ecological Information

Toxicity

- No data available

Persistence and degradability

- No data available

Bioaccumulative potential

- No data available

Mobility in Soil

- No data available

Other adverse effects

- According to test data on the components and the classification criteria for mixtures, this product has no known adverse effects on aquatic organisms.

Section 13 - Disposal Considerations

Waste treatment methods

Product waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations. Please be advised that state and local requirements for waste disposal may be more restrictive or otherwise different from federal laws and regulations.

Packaging waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations. Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Empty containers pose a fire risk, evaporate the residue under a fume hood. Rinse with an appropriate solvent.

Section 14 - Transport Information

	UN number	UN proper shipping name	Transport hazard class (es)	Packing group	Environmental hazards
DOT	Not regulated	NDA	NDA	NDA	NDA
TDG	Not regulated	NDA	NDA	NDA	NDA
IMO/MDG	Not regulated	NDA	NDA	NDA	NDA
IATA/ICAO	Not regulated	NDA	NDA	NDA	NDA

- Special precautions for user** • No data available
- Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** • No data available
- Other information**

- Transportation status: The listed Transportation Classification does not address all regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors.

Note: The above regulatory prescriptions are those valid on the date of the publication of this sheet. Given the possible evolution of transportation regulations for Hazardous materials, it would be advisable to check their validity with your sales office.

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications • Acute

United States

Environment

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities • Hydrogen peroxide	7722-84-1	Not Listed
U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs • Hydrogen peroxide	7722-84-1	1000 lb EPCRA RQ (concentration >52%)
U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs • Hydrogen peroxide	7722-84-1	1000 lb TPQ (concentration >52%)
U.S. - CERCLA/SARA - Section 313 - Emission Reporting • Hydrogen peroxide	7722-84-1	Not Listed

United States - California

Environment

U.S. - California - Proposition 65 - Carcinogens List • Hydrogen peroxide	7722-84-1	Not Listed
U.S. - California - Proposition 65 - Developmental Toxicity • Hydrogen peroxide	7722-84-1	Not Listed

Other Information

- All components of this product are listed on the following:
- US TSCA Inventory.

Section 16 - Other Information

- Last Revision Date** • 16/April/2015
- Preparation Date** • 16/April/2015
- Disclaimer/Statement of Liability** • The information provided in this Safety Data Sheet is correct to the best of our knowledge, information, and belief at the date of its publication. Such information is only given as a guidance to help the user handle, use, process, store, transport,

dispose, and release the product in satisfactory safety conditions and is not to be considered as a warranty or quality specification. It should be used in conjunction with technical sheets but does not replace them. Thus, the information only relates to the designated specific product and may not be applicable if such product is used in combination with other materials or in another manufacturing process, unless otherwise specifically indicated. It does not release the user from ensuring he is in conformity with all regulations linked to its activity.

Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene
IARC = International Agency for Research on Cancer
MSHA = Mine Safety and Health Administration
NIOSH = National Institute of Occupational Safety and Health

NTP = National Toxicology Program
OSHA = Occupational Safety and Health Administration
STEL = Short Term Exposure Limits are based on 15-minute exposures
TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product Identifier**

- Trade name Plexslick 957

1.2 Relevant identified uses of the substance or mixture and uses advised against**Uses advised against**

- For industrial use only.

1.3 Details of the supplier of the safety data sheet**Company**

Chemplex, Solvay Group
506 CR 137
Snyder, TX 97549
Phone: (325) 573-7298

1.4 Emergency telephone

FOR EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT CONTACT: CHEMTREC 800-424-9300 within the United States and Canada, or 703-527-3887 for international collect calls.

SECTION 2: Hazards Identification

Although OSHA has not adopted the environmental portion of the GHS regulations, this document may include information on environmental effects.

2.1 Classification of the substance or mixture**HCS 2012 (29 CFR 1910.1200)**

- Not a hazardous product according to Globally harmonized System (GHS)

2.2 Label elements**HCS 2012 (29 CFR 1910.1200)**

- Not a hazardous product according to Globally harmonized System (GHS)

2.3 Other hazards which do not result in classification

- Slightly irritating to eyes.
- Aspiration of the swallowed or vomited product can cause severe pulmonary complications.
- No specific risk when handled in accordance with good occupational hygiene and safety practice.
- Does NOT present any particular fire hazard.
- Hazardous reactions may occur on contact with certain chemicals. (Refer to the list of incompatible materials section 10: "Stability-Reactivity").

SECTION 3: Composition/information on ingredients**3.1 Substance**

- Not applicable, this product is a mixture.

3.2 Mixture

- Chemical nature Emulsion of petroleum distillate and aqueous solution.

Hazardous Ingredients and Impurities

Chemical Name	Identification number CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated light	64742-47-8	14 - 19

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

- Show this material safety data sheet to the doctor in attendance.
- First responder needs to protect himself.
- Place affected apparel in a sealed bag for subsequent decontamination.

In case of Inhalation

- Remove to fresh air.
- If breathing is difficult, give oxygen.
- If breathing has stopped, apply artificial respiration.
- Consult a physician if necessary.

In case of skin contact

- Wash off with soap and plenty of water.
- Remove contaminated clothing and shoes.
- Wash contaminated clothing before re-use.
- Call a physician if irritation develops or persists.

In case of eye contact

- Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
- Consult a physician if necessary.

In case of Ingestion

- Do NOT induce vomiting.
- Do not give anything to drink.
- Seek medical advice.
- Do not leave the victim unattended.
- Vomiting may occur spontaneously.
- Risk of product entering the lungs on vomiting after ingestion.
- Lay victim on side.

4.2 Most important symptoms and effects, both acute and delayed

Effects

- No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician

- All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

SECTION 5: Firefighting measures

Flash point	> 200 °F (> 93 °C) closed cup
	Flammability class: Will burn
Autoignition temperature	no data available
Flammability / Explosive limit	no data available

5.1 Extinguishing media**Suitable extinguishing media**

- Water mist
- Carbon dioxide (CO₂)
- Foam
- Dry chemical

Unsuitable extinguishing media

- Do not use a solid water stream as it may scatter and spread fire.

5.2 Special hazards arising from the substance or mixture**Specific hazards during fire fighting**

- Under fire conditions;
- Will burn
- (following evaporation of water)
- Harmful or toxic vapors are released.

Hazardous combustion products:

- Hazardous combustion products
- Carbon oxides
- Nitrogen oxides (NO_x)
- Sulfur oxides

5.3 Advice for firefighters**Special protective equipment for fire-fighters**

- Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing
- Firefighters should wear NIOSH/MSHA approved self-contained breathing apparatus and full protective clothing.

Specific fire fighting methods

- Cool closed containers exposed to fire with water spray.
- Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

- Avoid contact with the skin and the eyes.
- Wear suitable protective equipment.
- For personal protection see section 8.
- Stop the leak. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2 Environmental precautions

- Do not let product enter drains.
- Prevent product from entering sewage system.
- Spills may be reportable to the National Response Center (800-424-8802) and to state and/or local agencies

6.3 Methods and materials for containment and cleaning up**Recovery**

- Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
- Sweep up and shovel into suitable containers for disposal.
- Never return spills in original containers for re-use.

Decontamination / cleaning

- Clean contaminated surface thoroughly.
- Wash off with plenty of water.
- Recover the cleaning water for subsequent disposal.
- Decontaminate tools, equipment and personal protective equipment in a segregated area.

Disposal

- Dispose of in accordance with local regulations.

Additional advice

- Material can create slippery conditions.

6.4 Reference to other sections

- no data available

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

- Avoid inhalation, ingestion and contact with skin and eyes.
- Handle in accordance with good industrial hygiene and safety practice.

Hygiene measures

- Personal hygiene is an important work practice exposure control measure and the following general measures should be taken when working with or handling this materials:
 - 1) Do not store, use, and/or consume foods, beverages, tobacco products, or cosmetics in areas where this material is stored.
 - 2) Wash hands and face carefully before eating, drinking, using tobacco, applying cosmetics, or using the toilet.
 - 3) Wash exposed skin promptly to remove accidental splashes or contact with material.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

- Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems.
- Keep in a dry, cool and well-ventilated place.
- Keep container tightly closed.
- Do not freeze.
- Keep away from open flames, hot surfaces and sources of ignition.
- Keep away from incompatible materials to be indicated by the manufacturer

7.3 Specific end use(s)

- no data available

SECTION 8: Exposure controls/personal protection

Introductory Remarks: These recommendations provide general guidance for handling this product. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Assistance with selection, use and maintenance of worker protection equipment is generally available from equipment manufacturers.

8.1 Control parameters

Components with workplace occupational exposure limits

Ingredients	Value type	Value	Basis
Distillates (petroleum), hydrotreated light	TWA	200 mg/m ³	American Conference of Governmental Industrial Hygienists
Danger of cutaneous absorption Expressed as :as total hydrocarbon vapor			
Distillates (petroleum), hydrotreated light	TWA	500 ppm 2,000 mg/m ³	Occupational Safety and Health Administration - Table Z-1 Limits for Air Contaminants
The value in mg/m ³ is approximate.			

8.2 Exposure controls

Control measures

Engineering measures

- Effective exhaust ventilation system
- Where engineering controls are indicated by use conditions or a potential for excessive exposure exists, the following traditional exposure control techniques may be used to effectively minimize employee exposures :

Individual protection measures

Respiratory protection

- Use a respirator with an approved filter if a risk assessment indicates this is necessary.
- When respirators are required, select NIOSH/MSHA approved equipment based on actual or potential airborne concentrations and in accordance with the appropriate regulatory standards and/or industrial recommendations.

Hand protection

- Where there is a risk of contact with hands, use appropriate gloves
- Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
- Gloves must be inspected prior to use.

- Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Eye protection

- Safety glasses with side-shields
- Eye and face protection requirements will vary dependent upon work environment conditions and material handling practices. Appropriate ANSI Z87 approved equipment should be selected for the particular use intended for this material.
- Eye contact should be prevented through the use of:

Skin and body protection

- Remove and wash contaminated clothing before re-use.
- Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Protective suit
- Boots

Hygiene measures

- Personal hygiene is an important work practice exposure control measure and the following general measures should be taken when working with or handling this materials:
- 1) Do not store, use, and/or consume foods, beverages, tobacco products, or cosmetics in areas where this material is stored.
- 2) Wash hands and face carefully before eating, drinking, using tobacco, applying cosmetics, or using the toilet.
- 3) Wash exposed skin promptly to remove accidental splashes or contact with material.

Protective measures

- Ensure that eyewash stations and safety showers are close to the workstation location.
- The protective equipment must be selected in accordance with current local standards and in cooperation with the supplier of the protective equipment.
- Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the potential hazards, and/or risks that may occur during use.

SECTION 9: Physical and chemical properties

Physical and Chemical properties here represent typical properties of this product. Contact the business area using the Product information phone number in Section 1 for its exact specifications.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>	<u>Physical state:</u> liquid <u>Color:</u> white
<u>Odor</u>	oily
<u>Odor Threshold</u>	no data available
<u>pH</u>	not determined
<u>Boiling point/boiling range</u>	no data available
<u>Flash point</u>	> 200 °F (> 93 °C) closed cup

	Flammability class: Will burn
<u>Evaporation rate (Butylacetate = 1)</u>	no data available
<u>Flammability (solid, gas)</u>	no data available
<u>Flammability (liquids)</u>	no data available
<u>Flammability / Explosive limit</u>	no data available
<u>Autoignition temperature</u>	no data available
<u>Vapor pressure</u>	no data available
<u>Vapor density</u>	no data available
<u>Density</u>	1.02 - 1.11 g/cm ³ (25 °C)
<u>Solubility</u>	no data available
<u>Partition coefficient: n-octanol/water</u>	no data available
<u>Thermal decomposition</u>	no data available
<u>Viscosity</u>	no data available
<u>Explosive properties</u>	no data available
<u>Oxidizing properties</u>	no data available

9.2 Other information

no data available

SECTION 10: Stability and reactivity**10.1 Reactivity**

- no data available

10.2 Chemical stability

- Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions**Polymerization**

- Hazardous polymerization does not occur.

10.4 Conditions to avoid

- Heat, flames and sparks.

10.5 Incompatible materials

- Strong oxidizing agents

10.6 Hazardous decomposition productsPRCO90068264
Version: 1.00 / US (Z8)www.solvay.com

7 / 13

- On combustion or on thermal decomposition (following the evaporation of water) releases:
- Carbon oxides
- Nitrogen oxides (NOx)
- Sulfur oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Acute oral toxicity no data available

Acute inhalation toxicity no data available

Acute dermal toxicity no data available

Acute toxicity (other routes of administration) no data available

Skin corrosion/irritation

Not classified as irritating to skin
According to the data on the components

Serious eye damage/eye irritation

slight irritation

Respiratory or skin sensitization

Not classified as sensitizing by skin contact
According to the data on the components

Mutagenicity

Genotoxicity in vitro no data available

Genotoxicity in vivo no data available

Carcinogenicity

no data available

Ingredients	CAS-No.	Rating	Basis
Distillates (petroleum), hydrotreated light	64742-47-8	Confirmed animal carcinogen with unknown relevance to humans	ACGIH

This product does not contain any ingredient designated as probable or suspected human carcinogens by:

NTP
IARC
OSHA

Toxicity for reproduction and development

Toxicity to reproduction / fertility no data available

Developmental Toxicity/Teratogenicity no data available

STOT

STOT-single exposure no data available

STOT-repeated exposure no data available

Aspiration toxicity no data available

SECTION 12: Ecological Information

12.1 Toxicity no data available

12.2 Persistence and degradability**Biodegradation**

Biodegradability The product itself has not been tested.

12.3 Bioaccumulative potential no data available

12.4 Mobility in soil no data available

12.5 Results of PBT and vPvB assessment This mixture contains no substance considered to be persistent, bioaccumulating, and toxic (PBT).
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

12.6 Other adverse effects no data available

Ecotoxicity assessment

Acute aquatic toxicity This product has no known ecotoxicological effects.
According to the data on the components

Chronic aquatic toxicity This product has no known ecotoxicological effects.
According to the data on the components

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product Disposal**

- Chemical additions, processing or otherwise altering this material may make the waste management information presented in this SDS incomplete, inaccurate or otherwise inappropriate. Please be advised that state and local requirements for waste disposal may be more restrictive or otherwise different from federal laws and regulations. Consult state and local regulations regarding the proper disposal of this material.

Waste Code

- Environmental Protection Agency
- Hazardous Waste - NO

Advice on cleaning and disposal of packaging

- Completely empty the packaging prior to decontamination.
- Rinse with an appropriate solvent.
- Dispose of in accordance with local regulations.

Measure for waste avoidance or recovery

- Do not dispose of the product at a dump.

SECTION 14: Transport information**DOT**

not regulated

TDG

not regulated

NOM

no data available

IMDG

not regulated

IATA

not regulated

Note: The above regulatory prescriptions are those valid on the date of publication of this sheet. Given the possible evolution of transportation regulations for hazardous materials, it would be advisable to check their validity with your sales office.

SECTION 15: Regulatory information

15.1 Notification status

Inventory Information	Status
United States TSCA Inventory	On TSCA Inventory
Canadian Domestic Substances List (DSL)	All components of this product are on the Canadian DSL.
Australia Inventory of Chemical Substances (AICS)	On the inventory, or in compliance with the inventory
Japan, CSCL - Inventory of Existing and New Chemical Substances	On the inventory, or in compliance with the inventory
Korea, Korean Existing Chemicals Inventory (KECI)	On the inventory, or in compliance with the inventory
China, Inventory of Existing Chemical Substances in China (IECSC)	On the inventory, or in compliance with the inventory

15.2 Federal Regulations

US, EPA EPCRA SARA Title III

SARA HAZARD DESIGNATION SECTIONS 311/312 (40 CFR 370)

Fire Hazard	no
Reactivity Hazard	no
Sudden Release of Pressure Hazard	no
Acute Health Hazard	no
Chronic Health Hazard	no

Section 313 Toxic Chemicals (40 CFR 372.65)

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Section 302 Emergency Planning Extremely Hazardous Substance Threshold Planning Quantity (40 CFR 355)

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

Section 302 Emergency Planning Extremely Hazardous Substance Reportable Quantity (40 CFR 355)

Ingredients	CAS-No.	Reportable quantity
Oxirane	75-21-8	10 lb
Formaldehyde	50-00-0	100 lb

Section 304 Emergency Release Notification Reportable Quantity (40 CFR 355)

Ingredients	CAS-No.	Reportable quantity
Oxirane	75-21-8	10 lb
Formaldehyde	50-00-0	100 lb



SAFETY DATA SHEET

Plexslick 957

Revision Date 03/13/2015

US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

Ingredients	CAS-No.	Reportable quantity
Diethanolamine	111-42-2	100 lb
Oxirane	75-21-8	10 lb
1,4-Dioxane	123-91-1	100 lb
Formaldehyde	50-00-0	100 lb
Methanol	67-56-1	5000 lb
Acetaldehyde	75-07-0	1000 lb

15.3 State Regulations

US. California Safe Drinking Water & Toxic Enforcement Act (Proposition 65)

WARNING! This product contains a chemical known in the State of California to cause cancer.

Ingredients	CAS-No.
Diethanolamine	111-42-2
Oxirane	75-21-8
Acetaldehyde	75-07-0
1,4-Dioxane	123-91-1
Formaldehyde	50-00-0

WARNING: This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

Ingredients	CAS-No.
Methanol	67-56-1
Oxirane	75-21-8

SECTION 16: Other information

NFPA (National Fire Protection Association) - Classification

Health 0 minimal
 Flammability 1 slight
 Instability or Reactivity 0 minimal

HMIS (Hazardous Materials Identification System (Paint & Coating)) - Classification

Health 0 minimal
 Flammability 1 slight
 Reactivity 0 minimal
 PPE Determined by User; dependent on local conditions

Further information

- Product classified under the US GHS format.

Date Prepared: 03/13/2015

Key or legend to abbreviations and acronyms used in the safety data sheet

- TWA 8-hour, time-weighted average
- ACGIH American Conference of Governmental Industrial Hygienists
- OSHA Occupational Safety and Health Administration
- NTP National Toxicology Program

PRCG90068264
 Version: 1.00 / US (Z8)
 www.solvay.com





SAFETY DATA SHEET


Plexstick 957

Revision Date 03/13/2015

- IARC International Agency for Research on Cancer
- NIOSH National Institute for Occupational Safety and Health

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information, and belief at the date of its publication. Such information is only given as a guidance to help the user handle, use, process, store, transport, dispose, and release the product in satisfactory safety conditions and is not to be considered as a warranty or quality specification. It should be used in conjunction with technical sheets but do not replace them. Thus, the information only relates to the designated specific product and may not be applicable if such product is used in combination with other materials or in another manufacturing process, unless otherwise specifically indicated. It does not release the user from ensuring he is in conformity with all regulations linked to its activity.





Safety Data Sheet

Section 1: Identification

Product identifier

- Product Name** • Claymax
Synonyms • Product number: 00601

Relevant identified uses of the substance or mixture and uses advised against

- Recommended use** • Potassium chloride substitute in oil well treatment

Details of the supplier of the safety data sheet

- Manufacturer** • Chemplex | Solvay USA Inc. | Novecare Division
 506 CR 137
 P.O. Box 1071 Snyder, TX 79550
 United States
 www.chemplex.net
 SDS@chemplex.net
Telephone (General) • 325.573.7298

Emergency telephone number

- Manufacturer** • 800.424.9300 - CHEMTREC

Section 2: Hazard Identification

United States (US)

According to OSHA 29 CFR 1910.1200 HCS

Classification of the substance or mixture

- OSHA HCS 2012** • Classification criteria not met

Label elements

- OSHA HCS 2012**
Hazard statements • No label element(s) required

Other hazards

- OSHA HCS 2012** • This product is not considered hazardous under the U.S. OSHA 29 CFR 1910.1200 Hazard Communication Standard.

Canada

According to WHMIS

Classification of the substance or mixture

- WHMIS** • Classification criteria not met

Label elements


WHMIS

- No label element(s) required

Other hazards

WHMIS

- In Canada, the product mentioned above is not considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

Other information

See Section 12 for Ecological Information.

Section 3 - Composition/Information on Ingredients**Substances****Mixtures**

Composition					
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive	Comments
Ethanaminium, 2-hydroxy-N,N,N-trimethyl-, chloride	CAS:67-48-1	40% TO 70%	Ingestion/Oral-Rat LD50 • 3400 mg/kg	OSHA HCS 2012: Not Classified - Criteria not met	NDA
Water	CAS:7732-18-5	15% TO 40%	Ingestion/Oral-Rat LD50 • >90 mL/kg	OSHA HCS 2012: Not Hazardous	NDA

- Material does not meet the criteria of a mixture.

See Section 11 for Toxicological Information.

Section 4: First-Aid Measures**Description of first aid measures****Inhalation**

- Move victim to fresh air. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing.

Skin

- IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

Eye

- In case of contact with substance, immediately flush eyes with running water for at least 20 minutes.

Ingestion

- Do NOT induce vomiting. Get medical attention immediately.

Most important symptoms and effects, both acute and delayed

- Refer to Section 11 - Toxicological Information.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

- All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

Section 5: Fire-Fighting Measures

Extinguishing media

- Suitable Extinguishing Media** • LARGE FIRE: Water spray, fog or regular foam.
SMALL FIRES: Dry chemical, CO₂, water spray or regular foam.

- Unsuitable Extinguishing Media** • No data available.

Special hazards arising from the substance or mixture

- Unusual Fire and Explosion Hazards** • No unusual fire and explosion hazards known.

- Hazardous Combustion Products** • No data available.

Advice for firefighters

- Structural firefighters' protective clothing will only provide limited protection. Wear positive pressure self-contained breathing apparatus (SCBA).

Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

- Personal Precautions** • Wear appropriate personal protective equipment. Do not walk through spilled material.
- Emergency Procedures** • ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep unauthorized personnel away. Stay upwind. Ventilate closed spaces before entering.

Environmental precautions

- Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

- Containment/Clean-up Measures** • Stop leak if you can do it without risk.
Prevent entry into waterways, sewers, basements or confined areas.
SMALL SPILLS: Take up with sand or other non-combustible absorbent material and place into containers for later disposal.
LARGE SPILLS: Dike far ahead of liquid spill for later disposal.

Section 7 - Handling and Storage

Precautions for safe handling

- Handling** • Wear appropriate personal protective equipment. Avoid contact with skin and eyes. DO NOT ingest. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

- Storage** • Keep away from heat, ignition sources and strong oxidizing agents. Store in a cool, dry, well-ventilated place. Keep container closed when not in use. Avoid storing at elevated temperatures and freezing temperatures. Optimal storage temperature: 41-81 F; Ground all equipment containing material.

Section 8 - Exposure Controls/Personal Protection

Control parameters

- Exposure Limits/Guidelines** • No applicable exposure limits have been established for the components or the

material.

Exposure controls

Engineering Measures/Controls

- Facilities using or storing this material should be equipped with an eyewash and safety shower in close proximity to areas of storage and use. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Personal Protective Equipment

Pictograms



Respiratory

Eye/Face

Skin/Body

General Industrial Hygiene Considerations

Environmental Exposure Controls

- In case of insufficient ventilation, wear suitable respiratory equipment.
- Wear protective eyewear (goggles, face shield, or safety glasses).
- Wear appropriate gloves.
- Do not get in eyes or on skin or clothing. Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco.
- No data available

Section 9 - Physical and Chemical Properties

Information on Physical and Chemical Properties

Material Description			
Physical Form	Liquid	Appearance/Description	Colorless to yellow liquid with slight fish odor.
Color	Colorless to pale yellow.	Odor	Slight fish odor.
Odor Threshold	Data lacking		
General Properties			
Boiling Point	> 212 F(> 100 C)	Melting Point	Data lacking
Decomposition Temperature	Data lacking	pH	Near neutral (1% solution with water)
Specific Gravity/Relative Density	1.0856 Water=1	Water Solubility	100 %
Viscosity	Data lacking		
Volatility			
Vapor Pressure	Data lacking	Vapor Density	Not Defined
Evaporation Rate	Data lacking		
Flammability			
Flash Point	> 200 F(> 93.3333 C) Data lacking	UEL	Data lacking
LEL	Data lacking	Autoignition	Data lacking
Flammability (solid, gas)	Data lacking		
Environmental			
Octanol/Water Partition coefficient	Data lacking		

Section 10: Stability and Reactivity

Reactivity

- No dangerous reaction known under conditions of normal use.

Chemical stability

- Stable

Possibility of hazardous reactions

- Hazardous polymerization will not occur.

Conditions to avoid

- No data available.

Incompatible materials

- No data available.

Hazardous decomposition products

- No data available.

Section 11 - Toxicological Information

Information on toxicological effects

Components		
Ethanaminium, 2-hydroxy-N,N,N-trimethyl-, chloride (40% TO 70%)	67-48-1	Acute Toxicity: Ingestion/Oral-Rat LD50 • 3400 mg/kg; <i>Sense Organs and Special Senses:Eye:Chromodacyroffhea; Behavioral:Excitement; Lungs, Thorax, or Respiration:Respiratory depression</i>

GHS Properties	Classification
Acute toxicity	OSHA HCS 2012 • Classification criteria not met
Aspiration Hazard	OSHA HCS 2012 • Classification criteria not met
Carcinogenicity	OSHA HCS 2012 • Classification criteria not met
Germ Cell Mutagenicity	OSHA HCS 2012 • Classification criteria not met
Skin corrosion/Irritation	OSHA HCS 2012 • Classification criteria not met
Skin sensitization	OSHA HCS 2012 • Classification criteria not met
STOT-RE	OSHA HCS 2012 • Classification criteria not met
STOT-SE	OSHA HCS 2012 • Classification criteria not met
Toxicity for Reproduction	OSHA HCS 2012 • Classification criteria not met
Respiratory sensitization	OSHA HCS 2012 • Classification criteria not met
Serious eye damage/Irritation	OSHA HCS 2012 • Classification criteria not met

Route(s) of entry/exposure

- Inhalation, Skin, Eye, Ingestion

Potential Health Effects

Inhalation

Acute (Immediate)

- Under normal conditions of use, no health effects are expected.

Chronic (Delayed)

- No data available.

Skin

Acute (Immediate)

- Under normal conditions of use, no health effects are expected.

Chronic (Delayed)

- No data available.

Eye

- Acute (Immediate)
- Chronic (Delayed)

- Under normal conditions of use, no health effects are expected.
- No data available.

Ingestion

- Acute (Immediate)
- Chronic (Delayed)

- Under normal conditions of use, no health effects are expected.
- No data available.

Key to abbreviations
LD = Lethal Dose

Section 12 - Ecological Information

Toxicity

- Material data lacking.

Persistence and degradability

- Material data lacking.

Bioaccumulative potential

- Material data lacking.

Mobility in Soil

- Material data lacking.

Other adverse effects

- No studies have been found.

Section 13 - Disposal Considerations

Waste treatment methods

Product waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	UN number	UN proper shipping name	Transport hazard class (es)	Packing group	Environmental hazards
DOT	NDA	Not regulated	NDA	NDA	NDA
TDG	NDA	Not regulated	NDA	NDA	NDA
IATA/ICAO	NDA	Not regulated	NDA	NDA	NDA

Special precautions for user
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

- None known.
- Not relevant.

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications • None

State Right To Know

Component	CAS	MA	NJ	PA
Ethanaminium, 2-hydroxy-N,N,N-trimethyl-, chloride	67-48-1	No	No	No
Water	7732-18-5	No	No	No

Inventory

Component	CAS	Canada DSL	Canada NDSL	TSCA
Ethanaminium, 2-hydroxy-N,N,N-trimethyl-, chloride	67-48-1	Yes	No	Yes
Water	7732-18-5	Yes	No	Yes

Canada

Labor

Canada - WHMIS - Classifications of Substances

• Ethanaminium, 2-hydroxy-N,N,N-trimethyl-, chloride	67-48-1	Uncontrolled product according to WHMIS classification criteria (including 60%, 70%)
• Water	7732-18-5	Uncontrolled product according to WHMIS classification criteria

Canada - WHMIS - Ingredient Disclosure List

• Ethanaminium, 2-hydroxy-N,N,N-trimethyl-, chloride	67-48-1	Not Listed
• Water	7732-18-5	Not Listed

Environment

Canada - CEPA - Priority Substances List

• Ethanaminium, 2-hydroxy-N,N,N-trimethyl-, chloride	67-48-1	Not Listed
• Water	7732-18-5	Not Listed

United States

Labor

U.S. - OSHA - Process Safety Management - Highly Hazardous Chemicals

• Ethanaminium, 2-hydroxy-N,N,N-trimethyl-, chloride	67-48-1	Not Listed
• Water	7732-18-5	Not Listed

U.S. - OSHA - Specifically Regulated Chemicals

• Ethanaminium, 2-hydroxy-N,N,N-trimethyl-, chloride	67-48-1	Not Listed
• Water	7732-18-5	Not Listed

Environment

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants

• Ethanaminium, 2-hydroxy-N,N,N-trimethyl-, chloride	67-48-1	Not Listed
--	---------	------------

• Water	7732-18-5	Not Listed
U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities		
• Ethanaminium, 2-hydroxy-N,N,N-trimethyl-, chloride	67-48-1	Not Listed
• Water	7732-18-5	Not Listed
U.S. - CERCLA/SARA - Radionuclides and Their Reportable Quantities		
• Ethanaminium, 2-hydroxy-N,N,N-trimethyl-, chloride	67-48-1	Not Listed
• Water	7732-18-5	Not Listed
U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs		
• Ethanaminium, 2-hydroxy-N,N,N-trimethyl-, chloride	67-48-1	Not Listed
• Water	7732-18-5	Not Listed
U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPGs		
• Ethanaminium, 2-hydroxy-N,N,N-trimethyl-, chloride	67-48-1	Not Listed
• Water	7732-18-5	Not Listed
U.S. - CERCLA/SARA - Section 313 - Emission Reporting		
• Ethanaminium, 2-hydroxy-N,N,N-trimethyl-, chloride	67-48-1	Not Listed
• Water	7732-18-5	Not Listed
U.S. - CERCLA/SARA - Section 313 - PBT Chemical Listing		
• Ethanaminium, 2-hydroxy-N,N,N-trimethyl-, chloride	67-48-1	Not Listed
• Water	7732-18-5	Not Listed

United States - California

Environment		
U.S. - California - Proposition 65 - Carcinogens List		
• Ethanaminium, 2-hydroxy-N,N,N-trimethyl-, chloride	67-48-1	Not Listed
• Water	7732-18-5	Not Listed
U.S. - California - Proposition 65 - Developmental Toxicity		
• Ethanaminium, 2-hydroxy-N,N,N-trimethyl-, chloride	67-48-1	Not Listed
• Water	7732-18-5	Not Listed
U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)		
• Ethanaminium, 2-hydroxy-N,N,N-trimethyl-, chloride	67-48-1	Not Listed
• Water	7732-18-5	Not Listed
U.S. - California - Proposition 65 - No Significant Risk Levels (NSRL)		
• Ethanaminium, 2-hydroxy-N,N,N-trimethyl-, chloride	67-48-1	Not Listed
• Water	7732-18-5	Not Listed
U.S. - California - Proposition 65 - Reproductive Toxicity - Female		
• Ethanaminium, 2-hydroxy-N,N,N-trimethyl-, chloride	67-48-1	Not Listed
• Water	7732-18-5	Not Listed
U.S. - California - Proposition 65 - Reproductive Toxicity - Male		
• Ethanaminium, 2-hydroxy-N,N,N-trimethyl-, chloride	67-48-1	Not Listed
• Water	7732-18-5	Not Listed

United States - Pennsylvania

Labor

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

- Ethanaminium, 2-hydroxy-N,N,N-trimethyl-, chloride 67-48-1 Not Listed
- Water 7732-18-5 Not Listed

U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances

- Ethanaminium, 2-hydroxy-N,N,N-trimethyl-, chloride 67-48-1 Not Listed
- Water 7732-18-5 Not Listed

United States - Rhode Island

Labor

U.S. - Rhode Island - Hazardous Substance List

- Ethanaminium, 2-hydroxy-N,N,N-trimethyl-, chloride 67-48-1 Not Listed
- Water 7732-18-5 Not Listed

Section 16 - Other Information

Revision Summary

Date	MSDS No.	Changes
18/August/2014		• Section 1 changed. Changes include Company Name Change.

Last Revision Date

- 18/August/2014

Preparation Date

- 27/November/2013


Disclaimer/Statement of Liability

- The information provided in this Safety Data Sheet is correct to the best of our knowledge, information, and belief at the date of its publication. Such information is only given as a guidance to help the user handle, use, process, store, transport, dispose, and release the product in satisfactory safety conditions and is not to be considered as a warranty or quality specification. It should be used in conjunction with technical sheets but do not replace them. Thus, the information only relates to the designated specific product and may not be applicable if such product is used in combination with other materials or in another manufacturing process, unless otherwise specifically indicated. It does not release the user from ensuring he is in conformity with all regulations linked to its activity.

Key to abbreviations

NDA = No data available

Safety Data Sheet



Section 1: Identification

Product identifier

- Product Name** • **Ferriplex 66**
- Synonyms** • Acetic Acid Solution
- Product Code** • 00307
- Chemical Category** • Organic acids

Relevant identified uses of the substance or mixture and uses advised against

- Recommended use** • Petrochemical industry

Details of the supplier of the safety data sheet

- Manufacturer** • Chemplex | Solvay USA Inc. | Novicare Division
506 CR 137
P.O. Box 1071 Snyder, TX 79550
United States
www.chemplex.net
SDS@chemplex.net
- Telephone (General)** • 325.573.7298

Emergency telephone number

- Manufacturer** • 800.424.9300 - CHEMTREC

Section 2: Hazard Identification

United States (US)

According to: OSHA 29 CFR 1910.1200 HCS

Classification of the substance or mixture

- OSHA HCS 2012** • Skin Corrosion 1A
Serious Eye Damage 1

Label elements

OSHA HCS 2012

DANGER



- Hazard statements** • Causes severe skin burns and eye damage.
Causes serious eye damage

Precautionary statements

- Prevention** • Keep container tightly closed.
Keep only in original container.
Wash thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.
In case of inadequate ventilation wear respiratory protection.
- Response** • **IF ON SKIN (or hair):** Take off immediately all contaminated clothing. Rinse skin with water/shower.
Wash contaminated clothing before reuse.
IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a POISON CENTER or doctor/physician.
- Storage/Disposal** • Wash thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Other hazards

OSHA HCS 2012

- Acetic acid concentrated at elevated temperature may be corrosive to metals and evolve flammable hydrogen gas. Mists of weak acid solution in water may be irritating to the respiratory system.

Canada

According to: WHMIS

Classification of the substance or mixture

WHMIS

- Corrosive - E
Other Toxic Effects - D2B

Label elements

WHMIS



- Corrosive - E
Other Toxic Effects - D2B

Other hazards


WHMIS

- No other WHMIS hazards than those reported above.

Other information

- One should be specifically trained before communicating or using the following National Fire Protection Association (NFPA) and or Hazardous Materials Identification System (HMIS) categories since the definition and scales applied do not match US OSHA GHS and HAZCOM 2012 definitions and rules.

NFPA



- Health Hazard: 3 - Warning: Corrosive or toxic. Avoid skin contact or inhalation.
 - Flammability: 1 - Combustible if heated
 - Reactivity: 0 - Stable: Not reactive under normal conditions
- HMIS • HMIS Health - 2: Moderate Hazard
 HMIS Flammability - 1: Slight Hazard
 HMIS Physical Hazard - 0: Minimal Hazard

Section 3 - Composition/Information on Ingredients

Substances

- Not applicable. This material is a mixture.

Mixtures

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

Composition			
Chemical Name	Identifiers	%	Hazardous
Acetic acid	CAS:64-19-7	40% TO 50%	Yes
Citric acid	CAS:77-92-9	25% TO 30%	Yes

- This product is considered hazardous according to the OSHA Hazard Communication Standard 29 CFR 1910.1200. Under Canadian regulations (Workplace Hazardous Materials Information System (WHMIS) - Hazardous Products Act (HPA), this material is hazardous.

Section 4: First-Aid Measures

Description of first aid measures

- Inhalation** • Get medical attention immediately if symptoms occur. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- Skin** • Get medical attention immediately if symptoms occur. Rinse skin immediately with plenty of water for 15-20 minutes. Take off contaminated clothing and wash before reuse.
- Eye** • Flush eyes with water for at least 15 minutes while holding eyelids open. Get medical attention immediately. If easy to do, remove contact lenses, if worn.
- Ingestion** • Vomiting may occur spontaneously. To prevent aspiration of swallowed product, lay victim on side. Do NOT induce vomiting. Get medical attention immediately. Give nothing to drink.

Most important symptoms and effects, both acute and delayed

- Pain, irritation, redness or blistering of skin. May cause severe irritation and eye damage.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

- All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred. Treat symptomatically. There is no specific antidote available. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach.

Section 5: Fire-Fighting Measures

Extinguishing media

Suitable Extinguishing Media • LARGE FIRES: Dry chemical, CO₂, alcohol-resistant foam or water spray.
SMALL FIRES: Dry chemical, CO₂, water spray or alcohol-resistant foam.

Unsuitable Extinguishing Media • DO NOT use high volume water jet.

Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards • Corrosive
When heated to decomposition it emits acrid smoke and irritating fumes.

Hazardous Combustion Products • Carbon monoxide (CO), and Carbon dioxide (CO₂)
Hazardous combustion products may include a complex mixture of airborne solid and liquid particulates and gases (acrid smoke and irritating fumes).

Advice for firefighters

- Firefighters should wear NIOSH/MSHA approved self-contained breathing apparatus and full protective clothing.
Standard procedures for chemical fires.
Collect contaminated fire extinguishing materials separately. This must be not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Cool closed containers exposed to fire with water spray.
Refer to Section 8 - Exposure Controls/Personal Protection.

Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Personal Precautions • Contact may cause burns to skin and eyes. Wear suitable protective clothing. Ventilate the area. Refer to Section 8 - Exposure Controls/Personal Protection.

Emergency Procedures • Keep unauthorized personnel away. Avoid all contact. Strict hygiene. Ventilate closed spaces before entering. Stop leak if you can do it without risk.

Environmental precautions

- Spills may be reportable to the National Response Center (800-424-8802) and to state and or local agencies. Do not flush to sewer or allow to enter waterways. Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems.

Methods and material for containment and cleaning up

Containment/Clean-up Measures • Dike to collect large liquid spills.
Contain and recover liquid when possible.
Neutralize the residue with dilute solution of sodium carbonate.
Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.
Wash remainder with plenty of water.
Water will make area slippery.
Repeat cleaning process until the contaminated surface is no longer slippery.
Refer to Section 13 - Disposal Considerations.

Prohibited Materials • Strong alkalines and oxidizing materials. Sources of ignition - heat, sparks and open flames.

Reference to other sections

- Refer to Section 8 - Exposure Controls/Personal Protection.

Section 7 - Handling and Storage

Precautions for safe handling

Handling • Do not breathe (dust, vapor or spray mist). Avoid contact with skin and eyes. Wash thoroughly after handling. Use only in well ventilated areas. Do not breathe (dust, vapor or spray mist)

Conditions for safe storage, including any incompatibilities

Storage

- Store locked up. Keep only in the original container/package in a cool well-ventilated place. Store away from alkali(bases)and oxidizing agents. Avoid excessive heat.
- Reactive with strong bases and oxidizing agents. May be corrosive to metals.

Incompatible Materials or Ignition Sources

Refer to Section 8 - Exposure Controls/Personal Protection.

Section 8 - Exposure Controls/Personal Protection

Control parameters

Exposure Limits/Guidelines • Use only with adequate ventilation. Avoid all contact. Strict hygiene.

Exposure Limits/Guidelines			
	Result	ACGIH	OSHA
Acetic acid (64-19-7)	TWAs	10 ppm TWA	10 ppm TWA; 25 mg/m3 TWA

Exposure controls

Engineering Measures/Controls

- Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Personal Protective Equipment

Respiratory

Eye/Face

Skin/Body

General Industrial Hygiene Considerations

Environmental Exposure Controls

Additional Protection Measures

- When respirators are required, use NIOSH/MSHA approved equipment based on actual or potential airborne concentrations and in accordance with the appropriate regulatory standards and/or industrial recommendations.
- Wear tightly fitting safety goggles to protect from serious eye damage.
- Wear protective gloves/protective clothing/eye protection/face protection.
- Avoid all contact. Strict hygiene. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Keep away from food, drink and animal feeding stuffs.
- Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways.
- The protective equipment must be selected in accordance with local standards and in cooperation with the supplier of the protective equipment. Selection of the appropriate personal protective equipment should be based upon an evaluation of the performance characteristics of the protective equipment relative to the tasks to be performed, conditions present, duration of use, and the potential hazards, and/or risks that may occur during use. Emergency equipment should be immediately accessible, with instructions for use. Facilities using or storing this material should be equipped with an eyewash and safety shower in close proximity to areas of storage and use.

Section 9 - Physical and Chemical Properties

Information on Physical and Chemical Properties

Material Description			
Physical Form	Liquid	Color	Clear Colorless
Odor	Pungent, Vinegar-like.	Odor Threshold	0.48 ppm acetic acid
General Properties			
Boiling Point	None	Melting Point	None

Decomposition Temperature	None	pH	2 to 4
Specific Gravity/Relative Density	= 1.18 @ 25 C(77 F) Water=1	Density	9.67 lbs/gal
Water Solubility	Soluble	Viscosity	None
Volatility			
Vapor Pressure	None	Vapor Density	1.45 Air=1
Evaporation Rate	No data available		
Flammability			
Flash Point	> 200 F(- 93.3333 C) closed cup	UEL	None
LEL	None	Autoignition	463 C(865.4 F) acetic acid
Flammability (solid, gas)	None		
Environmental			
Octanol/Water Partition coefficient	None	Bioaccumulation Factor	None

Section 10: Stability and Reactivity

Reactivity

- Strong Bases, Strong oxidizing agents, Strong reducing agents.

Chemical stability

- This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

Possibility of hazardous reactions

- Hazardous polymerization will not occur.

Conditions to avoid

- Excess heat.

Incompatible materials

- Strong alkalines and oxidizing materials. Acetic acid concentrated at elevated temperature may be corrosive to metals and evolve flammable hydrogen gas.

Hazardous decomposition products

- Carbon monoxide (CO), and Carbon dioxide (CO2) Hazardous combustion products may include a complex mixture of airborne solid and liquid particulates and gases (acid smoke and irritating fumes)

Section 11 - Toxicological Information

Information on toxicological effects

GHS Properties	Classification
Acute toxicity	OSHA HCS 2012 • Acute Toxicity - Dermal - Classification criteria not met; Acute Toxicity - Inhalation - Classification criteria not met; Acute Toxicity - Oral - Classification criteria not met
Aspiration Hazard	OSHA HCS 2012 • Classification criteria not met
Carcinogenicity	OSHA HCS 2012 • Classification criteria not met
Germ Cell Mutagenicity	OSHA HCS 2012 • Classification criteria not met

Skin corrosion/Irritation	OSHA HCS 2012 - Skin Corrosion 1A
Skin sensitization	OSHA HCS 2012 - Classification criteria not met
STOT-RE	OSHA HCS 2012 - Classification criteria not met
STOT-SE	OSHA HCS 2012 - Classification criteria not met
Toxicity for Reproduction	OSHA HCS 2012 - Classification criteria not met
Respiratory sensitization	OSHA HCS 2012 - Classification criteria not met
Serious eye damage/Irritation	OSHA HCS 2012 - Serious Eye Damage 1

Medical Conditions Aggravated by Exposure

- None known.

Potential Health Effects

Inhalation

Acute (Immediate) • Classification criteria not met. Mists of weak acid solution in water may be irritating to the respiratory system.

Chronic (Delayed) • No data available

Skin

Acute (Immediate) • Causes severe skin burns and eye damage.

Chronic (Delayed) • No data available

Eye

Acute (Immediate) • Causes serious eye damage.

Chronic (Delayed) • No data available

Ingestion

Acute (Immediate) • May cause burns of the gastrointestinal tract if swallowed.

Chronic (Delayed) • No data available

Section 12 - Ecological Information

Toxicity

- No data available

Persistence and degradability

- No data available

Bioaccumulative potential

- No data available

Mobility in Soil

- No data available

Other adverse effects

- According to test data on the components and the classification criteria for mixtures, this product has no known adverse effects on aquatic organisms.

Section 13 - Disposal Considerations

Waste treatment methods

Product waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations. Please be advised that state and local requirements for

waste disposal may be more restrictive or otherwise different from federal laws and regulations.

Packaging waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations. Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Empty containers pose a fire risk, evaporate the residue under a fume hood. Rinse with an appropriate solvent.

Section 14 - Transport Information

	UN number	UN proper shipping name	Transport hazard class (es)	Packing group	Environmental hazards
DOT	UN2790	ACETIC ACID SOLUTION	8	II	NDA
TDG	UN2790	ACETIC ACID SOLUTION	8	II	NDA
IMO/IMDG	UN2790	ACETIC ACID SOLUTION	8	II	NDA
IATA/ICAO	UN2790	ACETIC ACID SOLUTION	8	II	NDA

Special precautions for user • No data available

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code • No data available

Other information

- Transportation status: The listed Transportation Classification does not address all regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors.

DOT • Dangerous Good Description: UN 2790 ACETIC ACID SOLUTION, 8, II

This product contains one or more ingredients identified as a hazardous substance in Appendix A of 49 CFR 172.101. The product quantity, in one package, which triggers the RQ requirements under 49 CFR for each ingredient is as follows:

Reportable quantities: RQ substance: Acetic acid RQ limit for substance: 5,000 lbs.

The Emergency Response Guidebook (ERG) number for the assigned proper shipping name is 153.

TDG • Dangerous Good Description: UN 2790 ACETIC ACID SOLUTION, 8, II

The Emergency Response Guidebook (ERG) number for the assigned proper shipping name is 153.

IMO/IMDG • Dangerous Good Description: UN 2790 ACETIC ACID SOLUTION, 8, II

IATA/ICAO • Dangerous Good Description: UN 2790 ACETIC ACID SOLUTION, 8, II

Note: The above regulatory prescriptions are those valid on the date of the publication of this sheet. Given the possible evolution of transportation regulations for Hazardous materials, it would be advisable to check their validity with your sales office.

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications • Acute

United States

Environment

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

• Acetic acid	64-19-7	5000 lb final RQ; 2270 kg final RQ
• Citric acid	77-92-9	Not Listed
U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs		
• Acetic acid	64-19-7	Not Listed
• Citric acid	77-92-9	Not Listed
U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPOs		
• Acetic acid	64-19-7	Not Listed
• Citric acid	77-92-9	Not Listed
U.S. - CERCLA/SARA - Section 313 - Emission Reporting		
• Acetic acid	64-19-7	Not Listed
• Citric acid	77-92-9	Not Listed

United States - California

Environment

U.S. - California - Proposition 65 - Carcinogens List

• Acetic acid	64-19-7	Not Listed
• Citric acid	77-92-9	Not Listed

U.S. - California - Proposition 65 - Developmental Toxicity

• Acetic acid	64-19-7	Not Listed
• Citric acid	77-92-9	Not Listed

Section 16 - Other Information

Last Revision Date

- 03/March/2015

Preparation Date

- 03/March/2015

Other Information

- All components of this product are listed on the following:

US TSCA Inventory

Canada Domestic Substance List (DSL)

Australia Inventory of Chemical Substances (AICS)

China Inventory of Existing chemical Substances in China (IECSC)

Japan Inventory of Existing and New Chemicals (ENCS)

Korea Existing Chemical Inventory (KECI)

Disclaimer/Statement of Liability

- The information provided in this Safety Data Sheet is correct to the best of our knowledge, information, and belief at the date of its publication. Such information is only given as a guidance to help the user handle, use, process, store, transport, dispose, and release the product in satisfactory safety conditions and is not to be considered as a warranty or quality specification. It should be used in conjunction with technical sheets but does not replace them. Thus, the information only relates to the designated specific product and may not be applicable if such product is used in combination with other materials or in another manufacturing process, unless otherwise specifically indicated. It does not release the user from ensuring he is in conformity with all regulations linked to its activity.

Key to abbreviations

Preparation Date: 03/March/2015
Revision Date: 03/March/2015

ACGIH = American Conference of Governmental Industrial Hygiene
IARC = International Agency for Research on Cancer
MSHA = Mine Safety and Health Administration
NIOSH = National Institute of Occupational Safety and Health

NTP = National Toxicology Program
OSHA = Occupational Safety and Health Administration
STEL = Short Term Exposure Limits are based on 15-minute exposures
TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures
